

PRODUCT-DETAILS

OT630KGCC3T

OT630KGCC3T Safety switch



General Information

Extended Product Type	OT630KGCC3T
Product ID	1SCA022277R1460
EAN	6417019063386
Catalog Description	OT630KGCC3T Safety switch
Long Description	The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. PE terminals included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340015M0004

Dimensions

Product Net Width	560 mm
Product Net Height	760 mm
Product Net Depth / Length	250 mm
Product Net Weight	24.53 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 570 A (500 V) 570 A (690 V) 570 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 570 A (500 V) 570 A (690 V) 570 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 315 kW (500 V) 400 kW (690 V) 560 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 570 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 80 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 20 kA
Power Loss	at Rated Operating Conditions per Pole 25 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Bottom In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Hole Diameter 12 mm Screw Clamp / PE Terminal 4pcs, 25...120 mm²
Cable Entry Position	Down/Down
Cable Outlets Per Side	2xII-flange / 2xII-flange
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	2 NO, 1 NC
Position of PE Terminals	Bottom In - Bottom Out

Environmental

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC340029D2704
Instructions and Manuals	1SCC340015M0004
RoHS Information	1SCC340049D0202

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	575 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	340 mm
Package Level 1 Gross Weight	26.7 kg
Package Level 1 EAN	6417019063386

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3642423

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

