

PRODUCT-DETAILS

## OS200BB2FCC3B OS200BB2FCC3B Enclosed switch fuse



Extended Product Type	OS200BB2FCC3B
Product ID	1SCA022280R9110
EAN	6417019066325
Catalog Description	OS200BB2FCC3B Enclosed switch fuse
Long Description	The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340004M0004

Mechanical Drawings	OTPK563818PII.stp
---------------------	-------------------

nensions	
Product Net Width	380 mm
Product Net Height	560 mm
Product Net Depth / Length	180 mm
Product Net Weight	13.6 kg

Technical	
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 415 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 415 V) 200 A (690 V) 200 A
Conventional Thermal Current (I <sub>the</sub> )	200 A
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	690 V
Power Loss	at Rated Operating Conditions per Pole 8 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Fuse Size	B1-B2
Fuse System	British Standard
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Hole Diameter 8 mm Screw Clamp / PE Terminal 2pcs, 1070 mm²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xII-flange / 2xII-flange
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 1 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Fuse Type	BS

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC340028D2703
Instructions and Manuals	1SCC340004M0004

RoHS Information	1SCC311108D0202
NOLIS IIIIOITIALIOII	130031110000202

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	565 mm
Package Level 1 Depth / Length	770 mm
Package Level 1 Height	330 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	6417019066325

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Enclosed Switches  $\rightarrow$  Enclosed Switch Fuses

