

PRODUCT-DETAILS

OS315BB3FCC3B

OS315BB3FCC3B Enclosed switch fuse



General Information

Extended Product Type	OS315BB3FCC3B
Product ID	1SCA022281R0380
EAN	6417019066387
Catalog Description	OS315BB3FCC3B Enclosed switch fuse
Long Description	The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340004M0004

Dimensions

Product Net Width	380 mm
Product Net Height	560 mm
Product Net Depth / Length	180 mm
Product Net Weight	13.33 kg

Technical

Rated Operational Current AC-22A (I_g)	(380 ... 415 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_g)	(380 ... 415 V) 315 A (690 V) 315 A
Conventional Thermal Current (I_{the})	315 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	690 V
Power Loss	at Rated Operating Conditions per Pole 19 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Fuse Size	B1-B3
Fuse System	British Standard
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Hole Diameter 10 mm Screw Clamp / PE Terminal 4pcs, 25...120 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xII-flange / 2xII-flange
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 1 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Fuse Type	BS

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC340031D2703
Instructions and Manuals	1SCC340004M0004

RoHS Information	1SCC311108D0202
------------------	-----------------

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	575 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	15.5 kg 34.17 lb
Package Level 1 EAN	6417019066387

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories	
Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch Fuses	

