

PRODUCT-DETAILS

OEZXP280C

OEZXP280C Cable entry plate



OEZXP280C
1SCA022338R5950
6417019160948
OEZXP280C Cable entry plate
Steel sheet cable entry plate for none EMC enclosures. Three C-type cable entry hole and knock outs for control cable.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC390001M0011

Dimensions	
Product Net Width	800 mm

Product Net Height	50 mm
Product Net Depth / Length	230 mm
Product Net Weight	3.4 kg

Technical	
Cable Outlets Per Side	4xC-flange, Knock-outs: 2x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm
Enclosure Material	Steel

Environmental	
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)	
Instructions and	1SCC390001M0011
Manuals	

Container Information	
Package Level 1 Units	bag 1 piece
Package Level 1 Width	230 mm
Package Level 1 Depth / Length	800 mm
Package Level 1 Height	50 mm
Package Level 1 Gross Weight	3.4 kg
Package Level 1 EAN	6417019160948

Classifications	
Object Classification Code	N/A
ETIM 5	EC000211 - Gland plate for small distribution boards/switchgear cabinets
ETIM 6	EC000211 - Gland plate for small distribution boards/switchgear cabinets
ETIM 7	EC000211 - Gland plate for small distribution boards/switchgear cabinets
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3642965

Categories

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Enclosed Switches} \rightarrow \textbf{Enclosed Change-over and Transfer Switches Accessories}$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Enclosed\ Switches \rightarrow Enclosed\ Safety\ Switches\ Accessories$ $Low\ Voltage\ Products\ and\ Systems \rightarrow Enclosed\ Switches \rightarrow Enclosed\ Switch\ Fuses\ Accessories$

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Enclosed Switches} \rightarrow \textbf{Enclosed Switch-Disconnectors Accessories}$

OEZXP280C 3

