

## PRODUCT-DETAILS

# OTL63B4M

## OTL63B4M Enclosed Switch Disconnecter



### General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OTL63B4M                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Product ID            | 1SCA022562R6140                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| EAN                   | 6417019180427                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Catalog Description   | OTL63B4M Enclosed Switch Disconnecter                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Long Description      | The enclosure of the OTL series is made of rigid alu-zinc coated steel with polyester powder coating. The enclosure has a hinged door, with door lock. The cover is interlocked, and can not be opened when switch is on. The interlock function can be defeated for thermographing. Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water exposure and Immersion in accordance with UL746C. The cable entries are of knock out types. Neutral and PE terminal included. |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85363030     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC340015C0201 |
| Instructions and Manuals          | 1SCC340006M0013 |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 150 mm |
| Product Net Height         | 200 mm |
| Product Net Depth / Length | 100 mm |
| Product Net Weight         | 1.8 kg |

## Technical

|                                                     |                                                                                                  |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-21A ( $I_e$ )       | (500 V) 80 A<br>(380 ... 415 V) 80 A<br>(690 V) 80 A                                             |
| Rated Operational Current<br>AC-22A ( $I_e$ )       | (380 ... 415 V) 80 A<br>(690 V) 80 A                                                             |
| Rated Operational Current<br>AC-23A ( $I_e$ )       | (380 ... 415 V) 75 A<br>(690 V) 20 A                                                             |
| Rated Operational Power<br>AC-23A ( $P_e$ )         | (380 ... 415 V) 37 kW<br>(500 V) 37 kW<br>(690 V) 18.5 kW                                        |
| Conventional Thermal<br>Current ( $I_{the}$ )       | Fully Enclosed 80 A                                                                              |
| Rated Insulation Voltage<br>( $U_i$ )               | acc. to IEC/EN 60664-1 750 V                                                                     |
| Rated Operational Voltage                           | Main Circuit 750 V                                                                               |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ ) | (690 V AC) 2.1 kA                                                                                |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )  | for 1 s 1.5 kA                                                                                   |
| Power Loss                                          | at Rated Operating Conditions per Pole 4.5 W                                                     |
| Pollution Degree                                    | 3                                                                                                |
| Handle Color                                        | Black                                                                                            |
| Handle Type                                         | Selector handle                                                                                  |
| Position of Line Terminals                          | Top In - Bottom Out                                                                              |
| Standards                                           | IEC 60947-1, -3                                                                                  |
| Number of Poles                                     | 4                                                                                                |
| Connecting Capacity Main<br>Circuit                 | Screw Clamp 1.5...35 mm <sup>2</sup><br>Screw Clamp / PE Terminal 2pcs, 1.5...25 mm <sup>2</sup> |
| Cable Entry Position                                | Up/Down                                                                                          |
| Cable Outlets Per Side                              | 2xø32.5+ø16.5 / 2xø32.5+ø16.5                                                                    |
| Degree of Protection                                | acc. to IEC 60529 IP65                                                                           |
| Enclosure Material                                  | Steel sheet                                                                                      |
| Maximum Mounted<br>Auxiliary Contacts               | 2 NO, 1 NC                                                                                       |
| Mounted Auxiliary<br>Contacts                       | 0 NO, 0 NC                                                                                       |
| Position of Neutral<br>Terminals                    | Top In - Bottom Out                                                                              |
| Position of PE Terminals                            | Top In - Bottom Out                                                                              |

---

## Environmental

---

RoHS Status

Following EU Directive 2011/65/EU

---

---

## Certificates and Declarations (Document Number)

---

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC340005D2704 |
| Instructions and Manuals          | 1SCC340006M0013 |
| RoHS Information                  | 1SCC340034D0203 |

---

---

## Container Information

---

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 162 mm        |
| Package Level 1 Depth /<br>Length | 222 mm        |
| Package Level 1 Height            | 148 mm        |
| Package Level 1 Gross<br>Weight   | 1.9 kg        |
| Package Level 1 EAN               | 6417019180427 |

---

---

## Classifications

---

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| UNSPSC                     | 39122233                                                   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

---

---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

