

## PRODUCT-DETAILS

# OTE36A4M

## OTE36A4M EMC safety switch



### General Information

|                       |                            |
|-----------------------|----------------------------|
| Extended Product Type | OTE36A4M                   |
| Product ID            | 1SCA022613R9360            |
| EAN                   | 6417019200026              |
| Catalog Description   | OTE36A4M EMC safety switch |

#### Long Description

The enclosure in the OTE series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal. The EMC protection is utilized by a metal plate in the bottom, connected to the cable shield with clamps, included in the delivery. No EMC glands needed.

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85363030     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                       |                 |
|-----------------------|-----------------|
| Data Sheet, Technical | 1SCC340015C0201 |
|-----------------------|-----------------|

## Information

|                          |                    |
|--------------------------|--------------------|
| Instructions and Manuals | 1SCC340003M0016    |
| Mechanical Drawings      | OTPK201490SM32.stp |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 145 mm  |
| Product Net Height         | 200 mm  |
| Product Net Depth / Length | 90 mm   |
| Product Net Weight         | 0.86 kg |

## Technical

|                                                     |                                                                                                  |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-22A ( $I_e$ )       | (380 ... 415 V) 63 A<br>(500 V) 63 A<br>(690 V) 63 A                                             |
| Rated Operational Current<br>AC-23A ( $I_e$ )       | (380 ... 415 V) 45 A<br>(500 V) 45 A<br>(690 V) 20 A                                             |
| Rated Operational Power<br>AC-23A ( $P_e$ )         | (380 ... 415 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 15 kW                                          |
| Conventional Thermal<br>Current ( $I_{the}$ )       | Fully Enclosed 80 A                                                                              |
| Rated Insulation Voltage<br>( $U_i$ )               | acc. to IEC/EN 60664-1 750 V                                                                     |
| Rated Operational Voltage                           | Main Circuit 750 V                                                                               |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ ) | (690 V AC) 2.1 kA                                                                                |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )  | for 1 s 1.5 kA                                                                                   |
| Power Loss                                          | at Rated Operating Conditions per Pole 4.5 W                                                     |
| Pollution Degree                                    | 3                                                                                                |
| Handle Color                                        | Red / Yellow                                                                                     |
| Handle Type                                         | Selector handle                                                                                  |
| Position of Line Terminals                          | Top In - Bottom Out                                                                              |
| Standards                                           | IEC 60947-1, -3                                                                                  |
| Special Functions                                   | EMC                                                                                              |
| Number of Poles                                     | 4                                                                                                |
| Connecting Capacity Main<br>Circuit                 | Screw Clamp 1.5...35 mm <sup>2</sup><br>Screw Clamp / PE Terminal 2pcs, 1.5...35 mm <sup>2</sup> |
| Cable Entry Position                                | Up/Down                                                                                          |
| Cable Outlets Per Side                              | 2xM32+M16 / 2xM32+M16                                                                            |
| Degree of Protection                                | acc. to IEC 60529 IP65                                                                           |
| Enclosure Material                                  | Plastic                                                                                          |
| Maximum Mounted<br>Auxiliary Contacts               | 2 NO, 2 NC                                                                                       |
| Mounted Auxiliary<br>Contacts                       | 1 NO, 0 NC                                                                                       |
| Position of Neutral<br>Terminals                    | Top In - Bottom Out                                                                              |

|                          |                     |
|--------------------------|---------------------|
| Position of PE Terminals | Top In - Bottom Out |
|--------------------------|---------------------|

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| BV Certificate                    | 1SCC340018D0204 |
| Declaration of Conformity<br>- CE | 1SCC340004D2705 |
| DNV GL Certificate                | 1SCC340045D0204 |
| Instructions and Manuals          | 1SCC340003M0016 |
| RoHS Information                  | 1SCC340066D0201 |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 162 mm        |
| Package Level 1 Depth /<br>Length | 222 mm        |
| Package Level 1 Height            | 148 mm        |
| Package Level 1 Gross<br>Weight   | 0.96 kg       |
| Package Level 1 EAN               | 6417019200026 |

## Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

