

PRODUCT-DETAILS

OS400D2FCC4B

OS400D2FCC4B Enclosed switch fuse



General Information

Extended Product Type	OS400D2FCC4B
Product ID	1SCA022628R6070
EAN	6417019204710
Catalog Description	OS400D2FCC4B Enclosed switch fuse
Long Description	The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for IJ-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. PE terminals included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340004M0004
Mechanical Drawings	OTPK765625P2II.stp

Dimensions

Product Net Width	560 mm
Product Net Height	760 mm
Product Net Depth / Length	250 mm
Product Net Weight	12.63 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (690 V) 400 A
Conventional Thermal Current (I_{the})	400 A
Rated Impulse Withstand Voltage (U_{imp})	14 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	690 V
Power Loss	at Rated Operating Conditions per Pole 30 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Fuse Size	0-2
Fuse System	DIN
Standards	IEC 60947-1, -3
Number of Poles	4
Connecting Capacity Main Circuit	Hole Diameter 10 mm Screw Clamp / PE Terminal 4pcs, 25...120 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xII-flange / 2xII-flange
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 1 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Fuse Type	DIN

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC340031D2703
Instructions and Manuals	1SCC340004M0004

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	575 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	14.8 kg 32.63 lb

Package Level 1 EAN

6417019204710

Classifications

Object Classification Code		Q
ETIM 5	EC000216 - Switch disconnecter	
ETIM 6	EC000216 - Switch disconnecter	
ETIM 7	EC000216 - Switch disconnecter	
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)	

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch Fuses

