


## PRODUCT-DETAILS

# OT200E40P

## OT200E40P SWITCH-DISCONNECTOR



### General Information

|                       |                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OT200E40P                                                                                                            |
| Product ID            | 1SCA022720R0400                                                                                                      |
| EAN                   | 6417019231310                                                                                                        |
| Catalog Description   | OT200E40P SWITCH-DISCONNECTOR                                                                                        |
| Long Description      | 4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals          | 1SCC301031M0220 |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 180.5 mm |
| Product Net Height         | 150 mm   |
| Product Net Depth / Length | 82.5 mm  |
| Product Net Weight         | 1.4 kg   |

## Technical

|                                                       |                                                                                     |
|-------------------------------------------------------|-------------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-21A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A<br>(1000 V) 200 A           |
| Rated Operational Current<br>AC-22A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A                             |
| Rated Operational Current<br>AC-23A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A                             |
| Rated Operational Power<br>AC-23A ( $P_e$ )           | (220 ... 240 V) 60 kW<br>(400 ... 415 V) 110 kW<br>(500 V) 132 kW<br>(690 V) 200 kW |
| Conventional Free-air<br>Thermal Current ( $I_{th}$ ) | $q = 40\text{ °C}$ 200 A                                                            |
| Conventional Thermal<br>Current ( $I_{the}$ )         | Fully Enclosed 200 A                                                                |
| Rated Impulse Withstand<br>Voltage ( $U_{imp}$ )      | 12 kV                                                                               |
| Rated Insulation Voltage<br>( $U_i$ )                 | acc. to IEC/EN 60664-1 1000 V                                                       |
| Rated Operational Voltage                             | Main Circuit 1000 V                                                                 |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ )   | (690 V) 30 kA                                                                       |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )    | for 1 s 8 kA                                                                        |
| Power Loss                                            | at Rated Operating Conditions per Pole 4.0 W                                        |
| Pollution Degree                                      | 3                                                                                   |
| Handle Color                                          | Black                                                                               |
| Handle Type                                           | Handle and shaft included                                                           |
| Fourth Pole Position                                  | Right Side                                                                          |
| Fourth Pole Type                                      | Switched - Simultaneous Function                                                    |
| Switches Operating<br>Mechanism                       | Mechanism at the End of the Switch<br>40 (Right Side)                               |
| Distance Between Phases                               | Standard                                                                            |
| Position of Line Terminals                            | Top In - Bottom Out<br>Bottom In - Top Out                                          |
| Operating Mode                                        | Front operated                                                                      |
| Standards                                             | IEC 60947-3                                                                         |
| Special Functions                                     | No                                                                                  |
| Mounting Type                                         | Base mounting                                                                       |
| Number of Poles                                       | 4                                                                                   |

|                       |                              |
|-----------------------|------------------------------|
| Degree of Protection  | Front IP00                   |
| Terminal Type         | Lug terminals                |
| Tightening Torque     | acc. IEC 60947-1 15...22 N·m |
| Mechanical Durability | 20000                        |
| Lock Type             | Yes                          |

## Environmental

|                           |                                   |
|---------------------------|-----------------------------------|
| RoHS Status               | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301149D0202                   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC301131D2705 |
| DNV GL Certificate                | 1SCC301174D0204 |
| Environmental Information         | 1SCC301149D0202 |
| Instructions and Manuals          | 1SCC301031M0220 |
| RoHS Information                  | 1SCC301149D0203 |

## Container Information

|                                   |                   |
|-----------------------------------|-------------------|
| Package Level 1 Units             | box 1 piece       |
| Package Level 1 Width             | 170 mm<br>6.69 in |
| Package Level 1 Depth /<br>Length | 190 mm<br>7.48 in |
| Package Level 1 Height            | 145 mm<br>5.71 in |
| Package Level 1 Gross<br>Weight   | 2.1 kg<br>0.93 lb |
| Package Level 1 EAN               | 6417019231310     |

## Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)         | 3661312                                                    |

## Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

