

PRODUCT-DETAILS

OS200D03N3

OS200D03N3 SWITCH FUSE



General Information

Extended Product Type	OS200D03N3
Product ID	1SCA022749R8460
EAN	6417019243528
Catalog Description	OS200D03N3 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,03 (Left Side),DIN,0,Handle and shaft not included,Detachable Neutral Link Integrated Into the Mechanism

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311093D0203
Instructions and Manuals	1SCC311012M0219

Dimensions

Product Net Width	220 mm
Product Net Height	199 mm

Product Net Depth / Length	149 mm
Product Net Weight	3.3 kg

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 60 kW (400 V) 110 kW (415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 200 A
Conventional Thermal Current (I_{the})	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 17 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Type	Detachable Neutral Link Integrated Into the Mechanism
Switches Operating Mechanism	03 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	0
Fuse System	DIN
Operating Mode	Front Operated
Standards	IEC 60947-3
Special Functions	Detachable Neutral
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	20 mm
Tightening Torque	15 ... 22 N·m
Fuse Type	DIN

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS200-250 2016
Declaration of Conformity - CE	1SCC311091D2704
DNV GL Certificate	1SCC311123D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC311012M0219
RoHS Information	1SCC311091D2704

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	210 mm
Package Level 1 Depth / Length	236 mm
Package Level 1 Height	163 mm
Package Level 1 Gross Weight	3.19 kg
Package Level 1 EAN	6417019243528

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

