


PRODUCT-DETAILS

OS400B13N2P

OS400B13N2P SWITCH FUSE



General Information

Extended Product Type	OS400B13N2P
Product ID	1SCA022754R8820
EAN	6417019245959
Catalog Description	OS400B13N2P SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,13 (Between the Poles),British Standard,B1-B4,Handle and shaft included,Switched - With Solid Link

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311100D0203
Instructions and Manuals	1SCC311015M0215

Dimensions

Product Net Width	318 mm
Product Net Height	230 mm

Product Net Depth / Length	176 mm
Product Net Weight	8.41 kg 18.54 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 132 kW (400 V) 220 kW (415 V) 230 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 400 A
Conventional Thermal Current (I_{the})	Fully Enclosed 400 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 14 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 45 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	13 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	B1-B4
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 ... 44 N·m
Fuse Type	BS

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations (Document Number)	
CCC Certificate	CCC OS315-400 2016
Declaration of Conformity - CE	1SCC311099D2704
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC311015M0215
RoHS Information	1SCC311099D2704

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	240 mm 9.45 in
Package Level 1 Depth / Length	335 mm 13.19 in
Package Level 1 Height	206 mm 8.11 in
Package Level 1 Gross Weight	8.81 kg 19.42 lb
Package Level 1 EAN	6417019245959

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

