

## PRODUCT-DETAILS

# OT200E03WC

## OT200E03WC CHANGE-OVER SWITCH



### General Information

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Extended Product Type | OT200E03WC                                    |
| Product ID            | 1SCA022767R8870                               |
| EAN                   | 6417019250564                                 |
| Catalog Description   | OT200E03WC CHANGE-OVER SWITCH                 |
| Long Description      | Handle and shaft has to be ordered separately |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC303003C0201 |
| Instructions and Manuals          | 1SCC303008M0203 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 194 mm |
| Product Net Height | 170 mm |

|                            |                    |
|----------------------------|--------------------|
| Product Net Depth / Length | 160 mm             |
| Product Net Weight         | 3.17 kg<br>6.99 lb |

## Technical

|                                                    |                                                            |
|----------------------------------------------------|------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-22A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-23A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-31B ( $I_e$ )         | (380 ... 415 V) 200 A                                      |
| Rated Operational Current AC-33B ( $I_e$ )         | (380 ... 415 V) 200 A                                      |
| Rated Operational Power AC-23A ( $P_e$ )           | (380 ... 415 V) 110 kW<br>(500 V) 132 kW<br>(690 V) 200 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | $q = 40^\circ\text{C}$ 200 A                               |
| Conventional Thermal Current ( $I_{the}$ )         | Fully Enclosed 200 A                                       |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 12 kV                                                      |
| Rated Insulation Voltage ( $U_i$ )                 | 1000 V                                                     |
| Rated Operational Voltage                          | 1000 V                                                     |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | for 1 s 8 kiloampere rms                                   |
| Power Loss                                         | 4 W                                                        |
| Pollution Degree                                   | 3                                                          |
| Handle Color                                       | Black                                                      |
| Handle Type                                        | Handle and shaft not included                              |
| Switches Operating Mechanism                       | Mechanism at the End of the Switch<br>03 (Left Side)       |
| Distance Between Phases                            | Wide phase distance                                        |
| Position of Line Terminals                         | Top In - Bottom Out, Bottom In - Top Out                   |
| Operating Mode                                     | Front operated                                             |
| Mounting Type                                      | Base mounting                                              |
| Number of Poles                                    | 3                                                          |
| Degree of Protection                               | Front IP20                                                 |
| Transition Type                                    | Open                                                       |

## Environmental

|                           |                 |
|---------------------------|-----------------|
| Environmental Information | 1SCC303050D0201 |
|---------------------------|-----------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC303002D0202 |
|--------------------------------|-----------------|

|                           |                 |
|---------------------------|-----------------|
| Environmental Information | 1SCC303050D0201 |
| Instructions and Manuals  | 1SCC303008M0203 |

Container Information

|                                |                    |
|--------------------------------|--------------------|
| Package Level 1 Units          | 1 piece            |
| Package Level 1 Width          | 186 mm<br>7.32 in  |
| Package Level 1 Depth / Length | 300 mm<br>11.81 in |
| Package Level 1 Height         | 185 mm<br>7.28 in  |
| Package Level 1 Gross Weight   | 3.44 kg<br>7.58 lb |
| Package Level 1 EAN            | 6417019250564      |

Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

