

PRODUCT-DETAILS

OS250B02

OS250B02 SWITCH FUSE



General Information	
Extended Product Type	OS250B02
Product ID	1SCA022769R9360
EAN	6417019251219
Catalog Description	OS250B02 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,2-pole,02 (Left Side),British Standard,B1-B3,Handle and shaft not included,

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311095D0203
Instructions and Manuals	1SCC311012M0219

Dimensions	
Product Net Width	199 mm
Product Net Height	133 mm

Product Net Depth / Length	130 mm
Product Net Weight	2.6 kg 5.6 lb

Technical	
Rated Operational	(500 V) 250 A
Current AC-21A (I _e)	(690 V) 250 A
Rated Operational Current AC-22A (I _e)	(380 415 V) 250 A (500 V) 250 A
Current AC-22A (le)	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-23A (I _e)	(500 V) 250 A
	(690 V) 250 A
Rated Operational Power AC-23A (P _e)	(220 240 V) 75 kW (400 V) 140 kW
AC-ESA (Fe)	(415 V) 145 kW
	(500 V) 170 kW
	(690 V) 250 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 250 A
Conventional Thermal	Fully Enclosed 250 A
Current (I _{the})	Tully Enclosed Eso A
Rated Impulse	12 kV
Withstand Voltage (U _{imp})	
Rated Insulation Voltage	1000 V
(U _i)	
Rated Operational	500 V
Voltage	f-u1 - 0 lill
Rated Short-time Withstand Current (I _{CW})	for 1 s 8 kiloampere rms
Rated Conditional Short-	(690 V) 80 kA
Circuit Current (Inc)	, ,
Power Loss	at Rated Operating Conditions per Pole 23 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	02 (Left Side)
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	
Fuse Size	B1-B3
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	2
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 44 N·m
Fuse Type	BS

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate CCC OS200-250 2016

Declaration of Conformity - CE	1SCC311095D2704
DNV GL Certificate	1SCC311123D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC311012M0219
RoHS Information	1SCC311095D2704

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	230 mm
	9.1 in
Package Level 1 Depth /	270 mm
Length	10.6 in
Package Level 1 Height	170 mm
	6.7 in
Package Level 1 Gross	2.9 kg
Weight	6.3 lb
Package Level 1 EAN	6417019251219

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Fuses

