

PRODUCT-DETAILS

OT400U04CP

OT400U04CP CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT400U04CP
Product ID	1SCA022771R2300
EAN	6417019251653
Catalog Description	OT400U04CP CHANGE-OVER SWITCH
Long Description	The change-over switches include a black handle IP65

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC303008M0201

Dimensions	
Product Net Width	305 mm
Product Net Height	185 mm

Product Net Depth /	203 mm
Length	
Product Net Weight	7 kg

Technical	
Rated Operational	(380 415 V) 400 A
Current AC-21A (I _e)	(500 V) 400 A (690 V) 400 A
Rated Operational	(380 415 V) 400 A
Current AC-22A (I _e)	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I _e)	(380 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B (I _e)	(380 415 V) 400 A
Rated Operational Current AC-33B (I _e)	(380 415 V) 400 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 400 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 15 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Mechanical Durability	8000 cycle
Transition Type	Open

Technical UL/CSA	
Horsepower Rating	(acc. to UL 240 V) 125 Hp
UL/CSA	(acc. to UL 480 V) 250 Hp
	(acc. to UL 600 V) 350 Hp
Ampere Rating UL/CSA	400 A

Environmental	
Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303007D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0201
RoHS Information	1SCC301149D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm
Package Level 1 Depth / Length	325 mm
Package Level 1 Height	218 mm
Package Level 1 Gross Weight	8.3 kg
Package Level 1 EAN	6417019251653

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

