

## PRODUCT-DETAILS

# OT800ELRR3AZ

## OT800ELRR3AZ Safety switch



### General Information

|                       |                            |
|-----------------------|----------------------------|
| Extended Product Type | OT800ELRR3AZ               |
| Product ID            | 1SCA022828R1180            |
| EAN                   | 6417019285467              |
| Catalog Description   | OT800ELRR3AZ Safety switch |

### Long Description

The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallell cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermographing.

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85363090     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC340015C0201 |
|-----------------------------------|-----------------|

Instructions and Manuals

1SCC340005M0007

Mechanical Drawings

OTKM104023P4R.stp

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 400 mm   |
| Product Net Height         | 1000 mm  |
| Product Net Depth / Length | 230 mm   |
| Product Net Weight         | 28.55 kg |

## Technical

|                                                     |                                                                                   |
|-----------------------------------------------------|-----------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-22A ( $I_e$ )       | (380 ... 415 V) 720 A<br>(500 V) 720 A<br>(690 V) 720 A                           |
| Rated Operational Current<br>AC-23A ( $I_e$ )       | (380 ... 415 V) 720 A<br>(500 V) 720 A<br>(690 V) 720 A                           |
| Rated Operational Power<br>AC-23A ( $P_e$ )         | (380 ... 415 V) 400 kW<br>(500 V) 500 kW<br>(690 V) 710 kW                        |
| Conventional Thermal<br>Current ( $I_{the}$ )       | Fully Enclosed 720 A                                                              |
| Rated Insulation Voltage<br>( $U_i$ )               | acc. to IEC/EN 60664-1 1000 V                                                     |
| Rated Operational Voltage                           | Main Circuit 1000 V                                                               |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ ) | (1000 V AC) 80 kA                                                                 |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )  | for 1 s 20 kA                                                                     |
| Power Loss                                          | at Rated Operating Conditions per Pole 40 W                                       |
| Pollution Degree                                    | 3                                                                                 |
| Handle Color                                        | Red / Yellow                                                                      |
| Handle Type                                         | Pistol handle                                                                     |
| Standards                                           | IEC 60947-1, -3                                                                   |
| Number of Poles                                     | 3                                                                                 |
| Connecting Capacity Main<br>Circuit                 | Hole Diameter 12 mm<br>Screw Clamp / PE Terminal 4pcs, 25...120 mm²               |
| Cable Entry Position                                | Up/Down                                                                           |
| Cable Outlets Per Side                              | 4xring-flange / 4xring-flange, Knock-outs: 3x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm |
| Degree of Protection                                | acc. to IEC 60529 IP65                                                            |
| Enclosure Material                                  | Steel sheet                                                                       |
| Maximum Mounted<br>Auxiliary Contacts               | 2 NO, 2 NC                                                                        |
| Mounted Auxiliary<br>Contacts                       | 2 NO, 1 NC                                                                        |

## Environmental

Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC340042D2703 |
| Instructions and Manuals          | 1SCC340005M0007 |
| RoHS Information                  | 1SCC340049D0202 |

Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 415 mm        |
| Package Level 1 Depth /<br>Length | 1110 mm       |
| Package Level 1 Height            | 325 mm        |
| Package Level 1 Gross<br>Weight   | 31 kg         |
| Package Level 1 EAN               | 6417019285467 |

Classifications

|                            |                                                             |
|----------------------------|-------------------------------------------------------------|
| Object Classification Code | Q                                                           |
| ETIM 5                     | EC000216 - Switch disconnecter                              |
| ETIM 6                     | EC000216 - Switch disconnecter                              |
| ETIM 7                     | EC000216 - Switch disconnecter                              |
| WEEE Category              | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

