

PRODUCT-DETAILS

## OS800B02

# OS800B02 SWITCH FUSE



General Information	
Extended Product Type	OS800B02
Product ID	1SCA022837R6560
EAN	6417019292045
Catalog Description	OS800B02 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,2-pole,02 (Left Side),British Standard,C1-C3,Handle and shaft not included.

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311113D0203
Instructions and Manuals	1SCC311016M0210

Dimensions	
Product Net Width	255 mm
Product Net Height	306 mm

Product Net Depth / Length	233 mm
Product Net Weight	10.264 kg 22.63 lb

Technical	_
Rated Operational	(500 V) 800 A
Current AC-21A (I <sub>e</sub> )	(690 V) 800 A
Rated Operational	(380 415 V) 800 A
Current AC-22A (I <sub>e</sub> )	(500 V) 800 A (690 V) 800 A
Rated Operational	(380 415 V) 800 A
Current AC-23A (I <sub>e</sub> )	(500 V) 800 A
	(690 V) 800 A
Rated Operational Power	(220 240 V) 250 kW
AC-23A (P <sub>e</sub> )	(400 V) 450 kW (415 V) 450 kW
	(500 V) 560 kW
	(690 V) 710 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 800 A
Conventional Thermal	Fully Enclosed 720 A
Current (I <sub>the</sub> )	Tally Enclosed 120 A
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub> )	
Rated Insulation Voltage	1000 V
$(U_i)$	
Rated Operational	500 V
Voltage	
Rated Short-time Withstand Current (I <sub>CW</sub> )	for 1 s 18 kiloampere rms
Rated Conditional Short-	(600 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Circuit Current (Inc)	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 65 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating	02 (Left Side)
Mechanism	
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	C1-C3
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	2
Terminal Type	Lug terminals
Terminal Width	39 mm
Tightening Torque	50 75 N·m
Fuse Type	BS 73 N. III

#### Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### **Certificates and Declarations (Document Number)**

CCC Certificate CCC OS630-800 2016

Declaration of Conformity - CE	1SCC311112D2704
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC311016M0210
RoHS Information	1SCC311112D2704

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm
Package Level 1 Depth / Length	365 mm
Package Level 1 Height	260 mm
Package Level 1 Gross Weight	11.044 kg 24.35 lb
Package Level 1 EAN	6417019292045

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

#### Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Fuses

