

PRODUCT-DETAILS

OS630B31N2

OS630B31N2 SWITCH FUSE



General Information

Extended Product Type	OS630B31N2
Product ID	1SCA022837R8850
EAN	6417019292267
Catalog Description	OS630B31N2 SWITCH FUSE
Long Description	Switch Fuses,Front operated,4-pole,31 (Between the Poles),British Standard,C1-C2,Handle and shaft not included,Switched - With Solid Link

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311112D0203
Instructions and Manuals	1SCC311016M0210

Dimensions

Product Net Width	431 mm
Product Net Height	306 mm

Product Net Depth / Length	233 mm
Product Net Weight	18.464 kg 40.71 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-23A (I_e)	(500 V) 630 A (380 ... 415 V) 630 A (690 V) 630 A
Rated Operational Current AC-23B (I_e)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 200 kW (400 V) 355 kW (415 V) 355 kW (500 V) 450 kW (690 V) 630 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 630 A
Conventional Thermal Current (I_{the})	Fully Enclosed 570 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 18 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 60 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	31 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	C1-C2
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Terminal Width	39 mm
Tightening Torque	50 ... 75 N·m
Fuse Type	BS

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS630-800 2016
Declaration of Conformity - CE	1SCC311112D2704
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_pd f
Instructions and Manuals	1SCC311016M0210
RoHS Information	1SCC311112D2704

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm 12.91 in
Package Level 1 Depth / Length	453 mm 17.83 in
Package Level 1 Height	260 mm 10.24 in
Package Level 1 Gross Weight	19.384 kg 42.73 lb
Package Level 1 EAN	6417019292267

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnectors
ETIM 5	EC001040 - Fuse switch disconnectors
ETIM 6	EC001040 - Fuse switch disconnectors
ETIM 7	EC001040 - Fuse switch disconnectors
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

