

PRODUCT-DETAILS

OTM160E3CM48D

OTM160E3CM48D MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM160E3CM48D
Product ID	1SCA022845R8450
EAN	6417019296500
Catalog Description	OTM160E3CM48D MOTORIZED C/O SWITCH
Long Description	OTM160E3CM48D MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

Dimensions	
Product Net Width	273 mm
Product Net Height	150 mm

Product Net Depth /	197 mm
Length	
Product Net Weight	5.6 kg

Technical		
Rated Operational	(380 415 V) 160 A	
Current AC-21A (I _e)	(500 V) 160 A	
	(690 V) 160 A	
Rated Operational Current AC-22A (I _e)	(380 415 V) 160 A (500 V) 160 A	
Current AC-22A (Ie)	(500 V) 160 A (690 V) 160 A	
Rated Operational	(380 415 V) 160 A	
Current AC-23A (I _e)	(500 V) 160 A	
	(690 V) 160 A	
Rated Operational Current AC-31B (I _e)	(380 415 V) 160 A	
Rated Operational	(380 415 V) 160 A	
Current AC-33B (I _e)		
Rated Operational Power	(380 415 V) 90 kW	
AC-23A (P _e)	(500 V) 110 kW (690 V) 160 kW	
Conventional Free-air	q = 40 °C 160 A	
Thermal Current (I _{th})	q-40 C100 A	
Conventional Thermal	Fully Enclosed 160 A	
Current (I _{the})	·	
Rated Impulse	12 kV	
Withstand Voltage (U _{imp}		
) Pated Insulation Voltage	1000 V	
Rated Insulation Voltage (U _i)	1000 V	
Rated Operational Voltage	1000 V	
Rated Short-time	for 1 s 8 kiloampere rms	
Withstand Current (I _{cw})		
Motor Operational	48 V DC	
Voltage		
Power Loss	2.4 W	
Pollution Degree	3	
Handle Color	Black	
Handle Type	Direct mounted handle	
Switches Operating Mechanism	Mechanism at the End of the Switch	
Distance Between Phases	Standard	
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out	
Operating Mode	Front operated	
Mounting Type	Base mounting	
Number of Poles	3	
Degree of Protection	Front IP20	
Transition Type	Open	
Transition Type	Орен	

Environmental

Environmental	1SCC303036D0202
Information	

Certificates and Declarations (Document Number)

Declaration of 1SCC303031D0201

OTM160E3CM48D

Conform	ity -	CE
---------	-------	----

Environmental	1SCC303036D0202
Information	
Instructions and	1SCC303002M0204
Manuals	
RoHS Information	1SCC303036D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	215 mm
Package Level 1 Depth / Length	395 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	6.9 kg
Package Level 1 EAN	6417019296500

Classifications		
Object Classification Code	Q	
ETIM 5	EC000216 - Switch disconnector	
ETIM 6	EC000216 - Switch disconnector	
ETIM 7	EC000216 - Switch disconnector	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Finland)	3641697	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ Change-over\ Switches$

