

PRODUCT-DETAILS

## **OTM315E3CM230C**OTM315E3CM230C MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM315E3CM230C
Product ID	1SCA022847R1210
EAN	6417019297804
Catalog Description	OTM315E3CM230C MOTORIZED C/O SWITCH
Long Description	OTM315E3CM230C MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

Dimensions	
Product Net Width	323 mm
Product Net Height	185 mm

Product Net Depth / Length	235 mm
Product Net Weight	8.2 kg 18.1 lb

Technical	
Rated Operational	(380 415 V) 315 A
Current AC-21A (I <sub>e</sub> )	(500 V) 315 A
	(690 V) 315 A
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 415 V) 315 A (500 V) 315 A
Current AC LLA (le)	(690 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-23A (I <sub>e</sub> )	(500 V) 315 A
	(690 V) 315 A
Rated Operational Current AC-31B (I <sub>e</sub> )	(380 415 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-33B (I <sub>e</sub> )	(300 123 4) 313 77
Rated Operational Power	(380 415 V) 160 kW
AC-23A (P <sub>e</sub> )	(500 V) 220 kW
	(690 V) 315 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 315 A
Conventional Thermal	Fully Enclosed 315 A
Current (I <sub>the</sub> )	Tany Enclosed 515 /
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	
)	
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 15 kiloampere rms
Motor Operational Voltage	220 240 V AC
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

## Environmental Environmental 1SCC303036D0202 Information

## **Certificates and Declarations (Document Number)**

OTM315E3CM230C 3

Declaration of Conformity - CE	1SCC303013D0202
Environmental Information	1SCC303036D0202
Instructions and Manuals	1SCC303002M0204
RoHS Information	1SCC303036D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	255 mm
Package Level 1 Depth / Length	460 mm
Package Level 1 Height	243 mm
Package Level 1 Gross Weight	10.22 kg
Package Level 1 EAN	6417019297804

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641744

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ Change-over\ Switches$ 

