

PRODUCT-DETAILS

OS200B21LRP

OS200B21LRP SPECIAL CONNECTED SWITCH FUSE



General Information

Extended Product Type	OS200B21LRP
Product ID	1SCA022854R3050
EAN	6417019303611
Catalog Description	OS200B21LRP SPECIAL CONNECTED SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,21 (Between the Poles),British Standard,B1-B2,Handle and shaft included,

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311119D0201
Instructions and Manuals	1SCC311019M0006

Dimensions

Product Net Width	353 mm
Product Net Height	150 mm

Product Net Depth / Length	184 mm
Product Net Weight	5.4 kg 11.9 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 60 kW (400 V) 110 kW (415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 200 A
Conventional Thermal Current (I_{the})	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 17 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Switches Operating Mechanism	21 (Between the Poles)
Position of Line Terminals	Left In - Right Out
Fuse Size	B1-B2
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	20 mm
Tightening Torque	15 ... 22 N·m
Fuse Type	BS

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS200-250_LR 2016
-----------------	-----------------------

Declaration of Conformity - CE	1SCC311119D2702
DNV GL Certificate	1SCC311132D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_p f
Instructions and Manuals	1SCC311019M0006
RoHS Information	1SCC311119D2702

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	215 mm 8.46 in
Package Level 1 Depth / Length	395 mm 15.55 in
Package Level 1 Height	215 mm 8.46 in
Package Level 1 Gross Weight	6.1 kg 13.45 lb
Package Level 1 EAN	6417019303611

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

