

## PRODUCT-DETAILS

# OS400B22LRP

## OS400B22LRP SPECIAL CONNECTED SWITCH FUSE



### General Information

|                       |                                                                                                                                    |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OS400B22LRP                                                                                                                        |
| Product ID            | 1SCA022855R2710                                                                                                                    |
| EAN                   | 6417019304588                                                                                                                      |
| Catalog Description   | OS400B22LRP SPECIAL CONNECTED SWITCH FUSE                                                                                          |
| Long Description      | Switch Fuses,Front Operated,4-pole,22 (Between the Poles),British Standard,B1-B4,Handle and shaft included,Switched - Fusible Pole |

### Ordering

|                       |              |
|-----------------------|--------------|
| Customs Tariff Number | 85365080     |
| Country of Origin     | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC311122D0201 |
| Instructions and Manuals          | 1SCC311018M0006 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 463 mm |
| Product Net Height | 194 mm |

|                            |         |
|----------------------------|---------|
| Product Net Depth / Length | 201 mm  |
| Product Net Weight         | 11.5 kg |

## Technical

|                                                      |                                                                                                |
|------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )           | (500 V) 400 A<br>(690 V) 400 A                                                                 |
| Rated Operational Current AC-22A ( $I_e$ )           | (380 ... 415 V) 400 A<br>(500 V) 400 A<br>(690 V) 400 A                                        |
| Rated Operational Current AC-23A ( $I_e$ )           | (380 ... 415 V) 400 A<br>(500 V) 400 A<br>(690 V) 400 A                                        |
| Rated Operational Power AC-23A ( $P_e$ )             | (220 ... 240 V) 132 kW<br>(400 V) 220 kW<br>(415 V) 230 kW<br>(500 V) 280 kW<br>(690 V) 400 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ )   | $q = 40\text{ °C}$ 400 A                                                                       |
| Conventional Thermal Current ( $I_{the}$ )           | Fully Enclosed 400 A                                                                           |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )        | 12 kV                                                                                          |
| Rated Insulation Voltage ( $U_i$ )                   | 1000 V                                                                                         |
| Rated Operational Voltage                            | 500 V                                                                                          |
| Rated Short-time Withstand Current ( $I_{cw}$ )      | for 1 s 14 kiloampere rms                                                                      |
| Rated Conditional Short-Circuit Current ( $I_{nc}$ ) | (690 V) 80 kA                                                                                  |
| Power Loss                                           | at Rated Operating Conditions per Pole 45 W                                                    |
| Pollution Degree                                     | 3                                                                                              |
| Handle Type                                          | Pistol handle and shaft included                                                               |
| Fourth Pole Type                                     | Switched - Fusible Pole                                                                        |
| Switches Operating Mechanism                         | 22 (Between the Poles)                                                                         |
| Position of Line Terminals                           | Left In - Right Out                                                                            |
| Fuse Size                                            | B1-B4                                                                                          |
| Fuse System                                          | British Standard                                                                               |
| Operating Mode                                       | Front Operated                                                                                 |
| Standards                                            | IEC 60947-3                                                                                    |
| Mounting Type                                        | Base mounting                                                                                  |
| Number of Poles                                      | 4                                                                                              |
| Terminal Type                                        | Lug terminals                                                                                  |
| Terminal Width                                       | 25 mm                                                                                          |
| Tightening Torque                                    | 30 ... 44 N·m                                                                                  |
| Fuse Type                                            | BS                                                                                             |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Certificates and Declarations (Document Number)

|                 |                       |
|-----------------|-----------------------|
| CCC Certificate | CCC OS315-400_LR 2016 |
|-----------------|-----------------------|

|                                   |                                                                   |
|-----------------------------------|-------------------------------------------------------------------|
| Declaration of<br>Conformity - CE | 1SCC311122D2702                                                   |
| DNV GL Certificate                | 1SCC311132D0202                                                   |
| EAC Certificate                   | EAC<br>OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf |
| Instructions and<br>Manuals       | 1SCC311018M0006                                                   |
| RoHS Information                  | 1SCC311122D2702                                                   |

Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 265 mm        |
| Package Level 1 Depth /<br>Length | 495 mm        |
| Package Level 1 Height            | 330 mm        |
| Package Level 1 Gross<br>Weight   | 11.5 kg       |
| Package Level 1 EAN               | 6417019304588 |

Classifications

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| Object Classification<br>Code | Q                                                          |
| ETIM 4                        | EC001040 - Fuse switch disconnecter                        |
| ETIM 5                        | EC001040 - Fuse switch disconnecter                        |
| ETIM 6                        | EC001040 - Fuse switch disconnecter                        |
| ETIM 7                        | EC001040 - Fuse switch disconnecter                        |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Fuses



