

PRODUCT-DETAILS

## OS400DS03

# OS400DS03 SWITCH FUSE



General Information	
Extended Product Type	OS400DS03
Product ID	1SCA022860R3480
EAN	6417019309057
Catalog Description	OS400DS03 SWITCH FUSE
Long Description	Switch Fuses, Side Operated, 3-pole, 03 (Left Side), DIN, 0, 1, 2, Handle and shaft not included

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311100D0203
Instructions and Manuals	1SCC311015M0215

Dimensions	
Product Net Width	288 mm
Product Net Height	230 mm

Product Net Depth / Length	193 mm
Product Net Weight	6.675 kg
	14.72 lb

Technical	
Rated Operational	(500 V) 400 A
Current AC-21A (I <sub>e</sub> )	(690 V) 400 A
Rated Operational	(380 415 V) 400 A
Current AC-22A (I <sub>e</sub> )	(500 V) 400 A
	(690 V) 400 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 415 V) 400 A (500 V) 400 A
current to Est (le)	(690 V) 400 A
Rated Operational Power	(220 240 V) 132 kW
AC-23A (P <sub>e</sub> )	(400 V) 220 kW
	(415 V) 230 kW
	(500 V) 280 kW (690 V) 400 kW
Conventional Free-air	q = 40 °C 400 A
Thermal Current (I <sub>th</sub> )	q 10 C 1007.
Conventional Thermal	Fully Enclosed 400 A
Current (I <sub>the</sub> )	·
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	
) Patrickly and the second street Valley as	10001
Rated Insulation Voltage (Ui)	1000 V
Rated Operational	500 V
Voltage	300 •
Rated Short-time	for 1 s 14 kiloampere rms
Withstand Current (I <sub>cw</sub> )	
Rated Conditional Short-	(690 V) 80 kA
Circuit Current (I <sub>nc</sub> )	
Power Loss	at Rated Operating Conditions per Pole 45 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating	03 (Left Side)
Mechanism	
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	0,1,2
	0,1,2 DIN
Fuse System	
Operating Mode	Side Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 44 N·m
Fuse Type	DIN

#### **Environmental**

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### **Certificates and Declarations (Document Number)**

CCC Certificate CCC OS315-400 2016

OS400DS03 3

Declaration of	1SCC311099D2704
Conformity - CE	
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC
	OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC311015M0215
RoHS Information	1SCC311099D2704

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm
	9.84 in
Package Level 1 Depth /	400 mm
Length	15.75 in
Package Level 1 Height	225 mm
	8.86 in
Package Level 1 Gross	7.255 kg
Weight	15.99 lb
Package Level 1 EAN	6417019309057

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3661153

#### Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Fuses

