

PRODUCT-DETAILS

OS315BS30OS315BS30 SWITCH FUSE



General Information	
Extended Product Type	OS315BS30
Product ID	1SCA022870R9390
EAN	6417019337791
Catalog Description	OS315BS30 SWITCH FUSE
Long Description	Switch Fuses, Side Operated, 3-pole, 30 (Right Side), British Standard, B1-B4, Handle and shaft not included,

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311099D0203
Instructions and Manuals	1SCC311015M0215

Dimensions	
Product Net Width	288 mm
Product Net Height	230 mm

Product Net Depth / Length	176 mm
Product Net Weight	6.675 kg 14.72 lb

Technical	
Rated Operational	(500 V) 315 A
Current AC-21A (I _e)	(690 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-22A (I _e)	(500 V) 315 A
	(690 V) 315 A
Rated Operational Current AC-23A (I _e)	(380 415 V) 315 A (500 V) 315 A
current to Est (le)	(690 V) 315 A
Rated Operational Power	(220 240 V) 100 kW
AC-23A (P _e)	(400 V) 160 kW
	(415 V) 180 kW
	(500 V) 220 kW (690 V) 315 kW
Conventional Free-air	q = 40 °C 315 A
Thermal Current (I _{th})	q 40 C31371
Conventional Thermal	Fully Enclosed 315 A
Current (I _{the})	·
Rated Impulse	12 kV
Withstand Voltage (U _{imp}	
)	4000
Rated Insulation Voltage (Ui)	1000 V
Rated Operational	500 V
Voltage	300 •
Rated Short-time	for 1 s 14 kiloampere rms
Withstand Current (I _{cw})	
Rated Conditional Short-	(690 V) 80 kA
Circuit Current (I _{nc})	
Power Loss	at Rated Operating Conditions per Pole 32 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating	30 (Right Side)
Mechanism	
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	B1-B4
	British Standard
Fuse System	
Operating Mode	Side Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 44 N·m
Fuse Type	BS

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate CCC OS315-400 2016

Declaration of Conformity - CE	1SCC311099D2704
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC311015M0215
RoHS Information	1SCC311099D2704

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm
	9.84 in
Package Level 1 Depth /	400 mm
Length	15.75 in
Package Level 1 Height	225 mm
	8.86 in
Package Level 1 Gross	7.255 kg
Weight	15.99 lb
Package Level 1 EAN	6417019337791

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Fuses

