


## PRODUCT-DETAILS

# OT1250E30W4

## OT1250E30W4 SWITCH-DISCONNECTOR



### General Information

|                       |                                                                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OT1250E30W4                                                                                                                                 |
| Product ID            | 1SCA022871R7650                                                                                                                             |
| EAN                   | 6417019338606                                                                                                                               |
| Catalog Description   | OT1250E30W4 SWITCH-DISCONNECTOR                                                                                                             |
| Long Description      | 3-pole, front operated, base mounted switch-diconnector, handle and shaft are not included, wide phase distance, terminal bolt kit included |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals          | 1SCC301047M0213 |

### Dimensions

|                   |          |
|-------------------|----------|
| Product Net Width | 454.5 mm |
|-------------------|----------|

|                            |          |
|----------------------------|----------|
| Product Net Height         | 306 mm   |
| Product Net Depth / Length | 145.5 mm |
| Product Net Weight         | 16.9 kg  |

## Technical

|                                                       |                                                                               |
|-------------------------------------------------------|-------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-21A ( $I_e$ )         | (380 ... 415 V) 1250 A<br>(500 V) 1250 A<br>(690 V) 1250 A<br>(1000 V) 1250 A |
| Rated Operational Current<br>AC-22A ( $I_e$ )         | (380 ... 415 V) 1250 A<br>(500 V) 1250 A<br>(690 V) 1250 A                    |
| Rated Operational Current<br>AC-23A ( $I_e$ )         | (380 ... 415 V) 1250 A<br>(500 V) 1250 A<br>(690 V) 1250 A                    |
| Rated Operational Power<br>AC-23A ( $P_e$ )           | (400 ... 415 V) 710 kW<br>(500 V) 900 kW<br>(690 V) 1200 kW                   |
| Conventional Free-air<br>Thermal Current ( $I_{th}$ ) | q = 40 °C 1250 A                                                              |
| Conventional Thermal<br>Current ( $I_{the}$ )         | Fully Enclosed 1250 A                                                         |
| Rated Impulse Withstand<br>Voltage ( $U_{imp}$ )      | 12 kV                                                                         |
| Rated Insulation Voltage<br>( $U_i$ )                 | acc. to IEC/EN 60664-1 1000 V                                                 |
| Rated Operational Voltage                             | Main Circuit 1000 V                                                           |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ )   | (690 V) 110 kA                                                                |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )    | for 1 s 50 kA                                                                 |
| Power Loss                                            | at Rated Operating Conditions per Pole 29 W                                   |
| Pollution Degree                                      | 3                                                                             |
| Handle Type                                           | Handle and shaft not included                                                 |
| Switches Operating<br>Mechanism                       | Mechanism at the End of the Switch<br>30 (Right Side)                         |
| Distance Between Phases                               | Phase distance 140 mm                                                         |
| Position of Line Terminals                            | Top In - Bottom Out<br>Bottom In - Top Out                                    |
| Operating Mode                                        | Front operated                                                                |
| Standards                                             | IEC 60947-3                                                                   |
| Special Functions                                     | Wide phase distance 140                                                       |
| Mounting Type                                         | Base mounting                                                                 |
| Number of Poles                                       | 3                                                                             |
| Degree of Protection                                  | Front IP00                                                                    |
| Terminal Type                                         | Lug terminals                                                                 |
| Tightening Torque                                     | acc. IEC 60947-1 50...75 N·m                                                  |
| Mechanical Durability                                 | 6000                                                                          |
| Lock Type                                             | No                                                                            |

## Environmental

|                           |                                   |
|---------------------------|-----------------------------------|
| RoHS Status               | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301149D0202                   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC301155D2704 |
| DNV GL Certificate                | 1SCC301184D0203 |
| Environmental Information         | 1SCC301149D0202 |
| Instructions and Manuals          | 1SCC301047M0213 |
| RoHS Information                  | 1SCC301149D0203 |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 400 mm        |
| Package Level 1 Depth /<br>Length | 613 mm        |
| Package Level 1 Height            | 170 mm        |
| Package Level 1 Gross<br>Weight   | 18.7 kg       |
| Package Level 1 EAN               | 6417019338606 |

## Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)         | 3661708                                                    |

## Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

