

PRODUCT-DETAILS

## OT400U30C

## OT400U30C CHANGE-OVER SWITCH



<b>General Information</b>	
Extended Product Type	OT400U30C
Product ID	1SCA022874R3220
EAN	6417019340210
Catalog Description	OT400U30C CHANGE-OVER SWITCH
Long Description	OT400U30C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Open transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions	
Product Net Width	251 mm

Product Net Height	185 mm
Product Net Depth / Length	203 mm
Product Net Weight	5.46 kg 12.04 lb

Technical	
Rated Operational Current AC-21A (I <sub>e</sub> )	(380 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational	(380 415 V) 400 A
Current AC-22A (I <sub>e</sub> )	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B (I <sub>e</sub> )	(380 415 V) 400 A
Rated Operational Current AC-33B (I <sub>e</sub> )	(380 415 V) 400 A
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 400 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 15 kiloampere rms
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism at the End of the Switch 30 (Right Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Mechanical Durability	8000 cycle
Transition Type	Open

Technical UL/CSA	
Horsepower Rating	(acc. to UL 480 V) 250 Hp
UL/CSA	(acc. to UL 240 V) 125 Hp
	(acc. to UL 600 V) 350 Hp
Ampere Rating UL/CSA	400 A

Environmental	
Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303004D2703
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0203

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm
	9.45 in
Package Level 1 Depth /	270 mm
Length	10.63 in
Package Level 1 Height	218 mm
	8.58 in
Package Level 1 Gross	5.87 kg
Weight	12.94 lb
Package Level 1 EAN	6417019340210

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

