

PRODUCT-DETAILS

## **OS250D03BB**

# OS250D03BB SPECIAL CONNECTED SWITCH FUSE



General Information	
Extended Product Type	OS250D03BB
Product ID	1SCA102197R1001
EAN	6417019369808
Catalog Description	OS250D03BB SPECIAL CONNECTED SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,03 (Left Side),DIN,0,1,Handle and shaft not included

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311120D0201
Instructions and Manuals	1SCC311019M0002

Dimensions	
Product Net Width	208 mm
Product Net Height	193 mm

OS250D03BB 2

Product Net Depth /	189 mm
Length	
Product Net Weight	4.3 kg

Technical	
Rated Operational	(500 V) 250 A
Current AC-21A (I <sub>e</sub> )	(690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-22A (I <sub>e</sub> )	(500 V) 250 A
Pated Operational	(690 V) 250 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 415 V) 250 A (500 V) 250 A
	(690 V) 250 A
Rated Operational Power	(220 240 V) 75 kW
AC-23A (P <sub>e</sub> )	(400 V) 140 kW
	(415 V) 145 kW (500 V) 170 kW
	(690 V) 250 kW
Conventional Free-air	q = 40 °C 250 A
Thermal Current (I <sub>th</sub> )	
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 250 A
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	
) Rated Insulation Voltage	1000 V
(U <sub>i</sub> )	1000 V
Rated Operational	500 V
Voltage	
Rated Short-time	for 1 s 8 kiloampere rms
Withstand Current (I <sub>cw</sub> )	
Rated Conditional Short- Circuit Current (I <sub>nc</sub> )	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 23 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	03 (Left Side)
Position of Line	Back In - Back Out
Terminals	
Fuse Size	0,1
Fuse System	DIN
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 44 N·m
Fuse Type	DIN

#### **Environmental**

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### **Certificates and Declarations (Document Number)**

Declaration of Conformity - CE

1SCC311120D2702

EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and	1SCC311019M0002
Manuals	
RoHS Information	1SCC311120D2702

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	240 mm 9.4 in
Package Level 1 Depth / Length	270 mm 10.6 in
Package Level 1 Height	218 mm 8.6 in
Package Level 1 Gross Weight	3.43 kg 7.6 lb
Package Level 1 EAN	6417019369808

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

#### Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Fuses

