

PRODUCT-DETAILS

## OT1000E12C

## OT1000E12C CHANGE-OVER SWITCH



| General Information   |  |
|-----------------------|--|
| Extended Product Type | OT1000E12C   |
| Product ID            | 1SCA103286R1001  |
| EAN                   | 6417019377995  |
| Catalog Description   | OT1000E12C CHANGE-OVER SWITCH  |
| Long Description      | OT1000E12C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, |

| Ordering               |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

| Popular Downloads                    |                 |
|--------------------------------------|-----------------|
| Data Sheet, Technical<br>Information | 1SCC303003C0201 |
| Instructions and<br>Manuals          | 1SCC303008M0203 |

| Dimensions        |        |
|-------------------|--------|
| Product Net Width | 400 mm |

| Product Net Height            | 306 mm          |
|-------------------------------|-----------------|
| Product Net Depth /<br>Length | 309 mm          |
| Product Net Weight            | 48 kg<br>400 lb |

| Technical   |   |
|---|---|
| Rated Operational<br>Current AC-21A (I <sub>e</sub> )       | (380 415 V) 1000 A<br>(500 V) 1000 A<br>(690 V) 1000 A  |
| Rated Operational<br>Current AC-22A (I <sub>e</sub> )       | (380 415 V) 1000 A<br>(500 V) 1000 A<br>(690 V) 1000 A  |
| Rated Operational<br>Current AC-23A (I <sub>e</sub> )       | (380 415 V) 1000 A<br>(500 V) 1000 A<br>(690 V) 1000 A  |
| Rated Operational<br>Current AC-31B (I <sub>e</sub> )       | (380 415 V) 1000 A                                      |
| Rated Operational<br>Current AC-33B (I <sub>e</sub> )       | (380 415 V) 1000 A                                      |
| Rated Operational Power<br>AC-23A (Pe)                      | (380 415 V) 560 kW<br>(500 V) 710 kW<br>(690 V) 1000 kW |
| Conventional Free-air<br>Thermal Current (I <sub>th</sub> ) | q = 40 °C 1000 A  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 12 kV   |
| Rated Insulation Voltage<br>(U <sub>1</sub> )               | 1000 V  |
| Rated Operational<br>Voltage                                | 1000 V  |
| Rated Short-time<br>Withstand Current (I <sub>cw</sub> )    | for 1 s 50 kiloampere rms                               |
| Power Loss  | 19 W  |
| Pollution Degree  | 3   |
| Handle Color  | Black   |
| Handle Type   | Handle and shaft not included                           |
| Switches Operating<br>Mechanism                             | Mechanism Between the Poles<br>12 (Between the Poles)   |
| Distance Between<br>Phases                                  | Standard  |
| Position of Line<br>Terminals                               | Top In - Bottom Out, Bottom In - Top Out                |
| Operating Mode  | Front operated  |
| Mounting Type   | Base mounting   |
| Number of Poles   | 3   |
| Degree of Protection  | Front IP20  |
| Transition Type   | Open  |

| Environmental |                 |
|---------------|-----------------|
| Environmental | 1SCC303050D0201 |
| Information   |                 |

| Certificates and Declarations (Document Number) |                 |
|---|-----------------|
| Declaration of<br>Conformity - CE               | 1SCC303015D2702 |
| Environmental                                   | 1SCC303050D0201 |

## Information

| Instructions and | 1SCC303008M0203 |
|------------------|-----------------|
| Manuals          |                 |

| Container Information           |               |
|---------------------------------|---------------|
| Package Level 1 Units           | 1 piece       |
| Package Level 1 Width           | 440 mm        |
| Package Level 1 Depth / Length  | 700 mm        |
| Package Level 1 Height          | 565 mm        |
| Package Level 1 Gross<br>Weight | 49 kg         |
| Package Level 1 EAN             | 6417019377995 |

| Classifications               |  |
|-------------------------------|--|
| Object Classification<br>Code | Q  |
| ETIM 5                        | EC000216 - Switch disconnector                             |
| ETIM 6                        | EC000216 - Switch disconnector                             |
| ETIM 7                        | EC000216 - Switch disconnector                             |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

