

PRODUCT-DETAILS

OT1600E22CP

OT1600E22CP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT1600E22CP
Product ID	1SCA103303R1001
EAN	6417019378084
Catalog Description	OT1600E22CP CHANGE-OVER SWITCH
Long Description	OT1600E22CP CHANGE-OVER SWITCH, Handle and shaft included, Open transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301049M0002

Dimensions

Product Net Width	480 mm
Product Net Height	372 mm

Product Net Depth / Length	309 mm
Product Net Weight	47.66 kg 105.07 lb

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 1600 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 1600 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 710 kW (500 V) 900 kW (690 V) 1200 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ }^{\circ}\text{C}$ 1600 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 50 kiloampere rms
Power Loss	48 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Terminal Width	50 mm
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Transition Type	Open

Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303015D2702
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC301049M0002
RoHS Information	1SCC301149D0202

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	394 mm 15.51 in
Package Level 1 Depth / Length	534 mm 21.02 in
Package Level 1 Height	368 mm 14.49 in
Package Level 1 Gross Weight	50.1 kg 110.45 lb
Package Level 1 EAN	6417019378084

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnect
ETIM 6	EC000216 - Switch disconnect
ETIM 7	EC000216 - Switch disconnect
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641575

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

