

PRODUCT-DETAILS

## OT250E23 OT250E23 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT250E23
Product ID	1SCA103714R1001
EAN	6417019380902
Catalog Description	OT250E23 SWITCH-DISCONNECTOR
Long Description	5-pole, front operated, base mounted switch-diconnector, handle and shaft are not included, terminal bolt kit included
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220
Dimensions	
Product Net Width	220.5 mm

Product Net Height	150 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	2.1 kg

Technical	
Rated Operational Current AC-21A (I <sub>e</sub> )	(380 415 V) 250 A (500 V) 250 A (690 V) 250 A (1000 V) 250 A
Rated Operational Current AC-21B ( $I_e$ )	(690 V) 250 A
Rated Operational Current DC-21B (I <sub>e</sub> )	(800 V) 250 A
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 250 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> )	(690 V) 30 kA
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism Between the Poles 23 (Between the Poles
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	5
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 1522 N·m
Mechanical Durability	20000
Lock Type	No

Environmentai	

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

## Certificates and Declarations (Document Number)

Declaration of Conformity	1SCC301163D2702
05	

OT250E23 3

DNV GL Certificate	1SCC301174D0204
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301031M0220
RoHS Information	1SCC301149D0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	190 mm 7.5 in
Package Level 1 Depth / Length	290 mm 11.4 in
Package Level 1 Height	110 mm 4.3 in
Package Level 1 Gross Weight	2.3 kg 5.1 lb
Package Level 1 EAN	6417019380902

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Disconnectors

