

PRODUCT-DETAILS

OT25F3C

OT25F3C CHANGE-OVER SWITCH



General Information

Extended Product Type	OT25F3C
Product ID	1SCA104863R1001
EAN	6417019390062
Catalog Description	OT25F3C CHANGE-OVER SWITCH
Long Description	OT25F3C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Open transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301054M0001

Dimensions

Product Net Width	70 mm
-------------------	-------

Product Net Height	68 mm
Product Net Depth / Length	68 mm
Product Net Weight	70 lb 0.25 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 20 A (500 V) 20 A (690 V) 11 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 9 kW (500 V) 9 kW (690 V) 9 kW
Conventional Free-air Thermal Current (I_{th})	$\varphi = 40^\circ\text{C}$ 32 A
Conventional Thermal Current (I_{the})	Fully Enclosed 32 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	750 V
Rated Operational Voltage	750 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 0.5 kiloampere rms
Power Loss	0.6 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	0.75 ... 10 mm ²
Degree of Protection	Front IP20
Transition Type	Open

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 200 V) 7.5 Hp (acc. to UL 480 V) 15 Hp (acc. to UL 240 V) 7.5 Hp (acc. to UL 208 V) 7.5 Hp (acc. to UL 600 V) 20 Hp
Ampere Rating UL/CSA	25 A

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303019D0201
Instructions and Manuals	1SCC301054M0001
RoHS Information	1SCC301183D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	80 mm
Package Level 1 Depth / Length	108 mm
Package Level 1 Height	79 mm
Package Level 1 Gross Weight	0.25 kg
Package Level 1 EAN	6417019390062

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601430
E-Number (Sweden)	3171261

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

