

PRODUCT-DETAILS

OT2500E12P OT2500E12P SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT2500E12F
Product ID	1SCA104978R1001
EAN	6417019391175
Catalog Description	OT2500E12P SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301078M0205
Mechanical Drawings	1SCC301522F0001 1SCC301521F0001 OT2500E12.iqs

OT2500E12P 2

Dimensions		
Product Net Width	472.5 mm	
Product Net Height	376.5 mm	
Product Net Depth / Length	145.5 mm	
Product Net Weight	25.8 kg	

Technical	
Rated Operational Current AC-21B (I _e)	(380 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Rated Operational Current AC-22B (I _e)	(380 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 2500 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 176 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 85 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Terminal Width	100 mm
Tightening Torque	acc. IEC 60947-1 5075 N·m
Mechanical Durability	6000
Lock Type	Yes

Environmental	
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and Declarations (Document Number)

Declaration of Conformity 1SCC301176D2702

OT2500E12P

- CE

DNV GL Certificate	1SCC301184D0203
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301078M0205
RoHS Information	1SCC301149D0203

Container Information		
Package Level 1 Units	box 1 piece	
Package Level 1 Width	580 mm	
Package Level 1 Depth / Length	780 mm	
Package Level 1 Height	500 mm	
Package Level 1 Gross Weight	27.7 kg	
Package Level 1 EAN	6417019391175	

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641588

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Disconnectors

