


PRODUCT-DETAILS

OT200U22CP

OT200U22CP Manual transfer switch



General Information

Extended Product Type	OT200U22CP
Product ID	1SCA105991R1001
EAN	6417019399096
Catalog Description	OT200U22CP Manual transfer switch
Long Description	The transfer switches include a black handle IP65 see the table below, Nema type 1, 3R, 12, a shaft and a bolt set for the cable connection.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0201

Dimensions

Product Net Width	237 mm
-------------------	--------

Product Net Height	150 mm
Product Net Depth / Length	160 mm
Product Net Weight	4.18 kg 9.22 lb

Technical

Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-31B (I _e)	(380 ... 415 V) 250 A
Rated Operational Current AC-33B (I _e)	(380 ... 415 V) 250 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 250 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 8 kiloampere rms
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Mechanical Durability	8000 cycle
Transition Type	Open

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 240 V) 75 Hp (acc. to UL 480 V) 150 Hp (acc. to UL 600 V) 200 Hp
Ampere Rating UL/CSA	200 A

Environmental

Environmental	1SCC303050D0201
---------------	-----------------

Information

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303006D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0201
RoHS Information	1SCC301149D0202

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	186 mm
Package Level 1 Depth / Length	310 mm
Package Level 1 Height	185 mm
Package Level 1 Gross Weight	4.45 kg 9.81 lb
Package Level 1 EAN	6417019399096

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

