

PRODUCT-DETAILS

OS600J02P

OS600J02P FUSIBLE DISCONNECT SWITCH



General Information

Extended Product Type	OS600J02P
Product ID	1SCA107595R1001
EAN	6417019410814
Catalog Description	OS600J02P FUSIBLE DISCONNECT SWITCH
Long Description	Switch Fuses,Front Operated,2-pole,02 (Left Side),Class J,600 A,Handle and shaft included,

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311016M0210

Dimensions

Product Net Width	255 mm
Product Net Height	306 mm

Product Net Depth / Length	233 mm
Product Net Weight	10.3 kg

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 200 kW (400 V) 355 kW (415 V) 355 kW (500 V) 450 kW (690 V) 630 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 630 A
Conventional Thermal Current (I_{the})	Fully Enclosed 570 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 18 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 60 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Switches Operating Mechanism	02 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	600 A
Fuse System	Class J
Operating Mode	Front Operated
Standards	UL98 IEC 60947-3
Mounting Type	Base mounting
Number of Poles	2
Terminal Type	Lug terminals
Terminal Width	39 mm
Fuse Type	J

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 240 V) 200 Hp (acc. to UL 480 V) 400 Hp (acc. to UL 600 V) 500 Hp
Ampere Rating UL/CSA	600 A
Tightening Torque UL/CSA	Wire-Clamp 500 in-lb Cable Lug 480 in-lb

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS630-800 2016
Declaration of Conformity - CE	1SCC311112D2704
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM.pdf
Instructions and Manuals	1SCC311016M0210
RoHS Information	1SCC311112D2704

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm
Package Level 1 Depth / Length	365 mm
Package Level 1 Height	260 mm
Package Level 1 Gross Weight	10.3 kg
Package Level 1 EAN	6417019410814

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

