


1SCC301735F0002

1SCC301734F0002

PRODUCT-DETAILS

Mechanical Drawings

OT2500E03K OT2500E03K SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT2500E03K
Product ID	1SCA108361R1001
EAN	6417019416779
Catalog Description	OT2500E03K SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted switch-diconnector with black direct mount handle, terminal bolt kit included
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301078M0205

Dimensions	
Product Net Width	472.5 mm
Product Net Height	376.5 mm
Product Net Depth / Length	167 mm
Product Net Weight	22.8 kg
Technical	
Rated Operational Current AC-21B (I _e)	(380 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Rated Operational Current AC-22B (I _e)	(380 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 2500 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 176 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 85 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted pistol type handle
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 5075 N⋅m
Mechanical Durability	6000
Lock Type	Yes

Environmental

RoHS Status Following EU Directive 2011/65/EU

Environmental Information 1SCC301149D0202

Certificates and Declarations (Document Number)		
Declaration of Conformity - CE	1SCC301176D2702	
DNV GL Certificate	1SCC301184D0203	
Environmental Information	1SCC301149D0202	
Instructions and Manuals	1SCC301078M0205	
RoHS Information	1SCC301149D0203	

Container Information		
Package Level 1 Units	box 1 piece	
Package Level 1 Width	394 mm	
Package Level 1 Depth / Length	534 mm	
Package Level 1 Height	368 mm	
Package Level 1 Gross Weight	46.9 kg	
Package Level 1 EAN	6417019416779	

Classifications		
Object Classification Code	Q	
ETIM 5	EC000216 - Switch disconnector	
ETIM 6	EC000216 - Switch disconnector	
ETIM 7	EC000216 - Switch disconnector	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Finland)	3660822	

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Disconnectors

