


PRODUCT-DETAILS

OT1000E22W4

OT1000E22W4 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT1000E22W4
Product ID	1SCA108500R1001
EAN	6417019418537
Catalog Description	OT1000E22W4 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector, wide phase distance, handle and shaft are not included, terminal bolt kit included

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301047M0213
Mechanical Drawings	OT1250E22W4

Dimensions

Product Net Width	594.5 mm
Product Net Height	306 mm
Product Net Depth / Length	145.5 mm
Product Net Weight	22.2 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A (1000 V) 1000 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P_e)	(400 ... 415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 1000 A
Conventional Thermal Current (I_{the})	Fully Enclosed 1000 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 92 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 50 kA
Power Loss	at Rated Operating Conditions per Pole 19 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Distance Between Phases	Phase distance 140 mm
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	Wide phase distance 140
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals

Tightening Torque	acc. IEC 60947-1 50...75 N·m
Mechanical Durability	6000
Lock Type	No

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301155D2704
DNV GL Certificate	1SCC301184D0203
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301047M0213
RoHS Information	1SCC301149D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	400 mm
Package Level 1 Depth / Length	613 mm
Package Level 1 Height	170 mm
Package Level 1 Gross Weight	23.9 kg
Package Level 1 EAN	6417019418537

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

