

PRODUCT-DETAILS

OT200E13CFP

OT200E13CFP CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT200E13CFP
Product ID	1SCA108543R1001
EAN	6417019399904
Catalog Description	OT200E13CFP CHANGE-OVER SWITCH
Long Description	OT200E13CFP CHANGE-OVER SWITCH, Handle and shaft included, Fast transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

205 mm
150 mm

Product Net Depth / Length	160 mm
Product Net Weight	3.915 kg 8.63 lb

Technical	
Rated Operational	(380 415 V) 200 A
Current AC-21A (I _e)	(500 V) 200 A
	(690 V) 200 A
Rated Operational	(380 415 V) 200 A
Current AC-22A (I _e)	(500 V) 200 A
	(690 V) 200 A
Rated Operational Current AC-23A (I _e)	(380 415 V) 200 A (500 V) 200 A
Current AC 25A (1g)	(690 V) 200 A
Rated Operational	(380 415 V) 200 A
Current AC-31B (I _e)	,
Rated Operational	(380 415 V) 200 A
Current AC-33B (I _e)	
Rated Operational Power	(380 415 V) 110 kW
AC-23A (P _e)	(500 V) 132 kW
	(690 V) 200 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 200 A
Conventional Thermal	Fully Englaced 200 A
Current (I _{the})	Fully Enclosed 200 A
Rated Impulse	12 kV
Withstand Voltage (U _{imp}	IL KV
)	
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time	for 1 s 8 kiloampere rms
Withstand Current (I _{cw})	
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating	Mechanism Between the Poles
Mechanism	13 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Transition Type	Fast
Transferringe	Fast

Environmental

Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303002D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301149D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	186 mm
	7.32 in
Package Level 1 Depth /	300 mm
Length	11.81 in
Package Level 1 Height	185 mm
	7.28 in
Package Level 1 Gross	4.215 kg
Weight	9.29 lb
Package Level 1 EAN	6417019399904

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641668

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

