

PRODUCT-DETAILS

# **OT250E12CL**OT250E12CL CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT250E12CL
Product ID	1SCA108610R1001
EAN	6417019397610
Catalog Description	OT250E12CL CHANGE-OVER SWITCH
Long Description	OT250E12CL CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Closed transition

1 piece
85365080
Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions	
Product Net Width	170 mm

Product Net Height	150 mm
Product Net Depth /	160 mm
Length	
Product Net Weight	2.93 kg
	6.46 lb

Technical	
Rated Operational	(380 415 V) 250 A
Current AC-21A (I <sub>e</sub> )	(500 V) 250 A
	(690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-22A (I <sub>e</sub> )	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-23A (I <sub>e</sub> )	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-31B (I <sub>e</sub> )	
Rated Operational Current AC-33B (I <sub>e</sub> )	(380 415 V) 250 A
Rated Operational Power	(380 415 V) 140 kW
AC-23A (P <sub>e</sub> )	(500 V) 170 kW
	(690 V) 250 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 250 A
Conventional Thermal	Fully Enclosed 250 A
Current (I <sub>the</sub> )	
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub> )	
Rated Insulation Voltage	1000 V
(U <sub>i</sub> )	1000 V
Rated Operational	1000 V
Voltage	
Rated Short-time	for 1 s 8 kiloampere rms
Withstand Current (I <sub>cw</sub> )	
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Distance Between Phases	Standard
Position of Line	Ton In Pottom Out Pottom In Ton Out
Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Closed

### **Environmental**

Environmental	1SCC303050D0201
Information	

# **Certificates and Declarations (Document Number)**

Declaration of 1SCC303045D2702

### Conformity - CE

Environmental Information	1SCC303050D0201
Instructions and	1SCC303008M0203
Manuals	

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	186 mm
	7.32 in
Package Level 1 Depth /	300 mm
Length	11.81 in
Package Level 1 Height	185 mm
	7.28 in
Package Level 1 Gross	3.2 kg
Weight	
Package Level 1 EAN	6417019397610

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

# Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches \rightarrow Cha$ 

