

PRODUCT-DETAILS

OT250E22CLP

OT250E22CLP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT250E22CLP
Product ID	1SCA108625R1001
EAN	6417019399294
Catalog Description	OT250E22CLP CHANGE-OVER SWITCH
Long Description	OT250E22CLP CHANGE-OVER SWITCH, Handle and shaft included, Closed transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions

Product Net Width	205 mm
Product Net Height	150 mm

Product Net Depth / Length	160 mm
Product Net Weight	205 lb 4.1 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 250 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 250 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 140 kW (500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Transition Type	Closed

Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303045D2702
--------------------------------	-----------------

Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301149D0202

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	186 mm 7.32 in
Package Level 1 Depth / Length	300 mm 11.81 in
Package Level 1 Height	185 mm 7.28 in
Package Level 1 Gross Weight	4.1 kg
Package Level 1 EAN	6417019399294

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

