

PRODUCT-DETAILS

## **OT315E04CF**

## OT315E04CF CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT315E04CF
Product ID	1SCA108631R1001
EAN	6417019401966
Catalog Description	OT315E04CF CHANGE-OVER SWITCH
Long Description	OT315E04CF CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Fast transition

Ordering	_
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions	
Product Net Width	265 mm

Product Net Height	185 mm
Product Net Depth /	203 mm
Length	
Product Net Weight	7.095 kg
	15.64 lb

Technical	
Rated Operational	(380 415 V) 315 A
Current AC-21A (I <sub>e</sub> )	(500 V) 315 A
	(690 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-22A (I <sub>e</sub> )	(500 V) 315 A (690 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-23A (I <sub>e</sub> )	(500 V) 315 A
, <del>-,</del>	(690 V) 315 A
Rated Operational	(380 415 V) 315 A
Current AC-31B (I <sub>e</sub> )	
Rated Operational	(380 415 V) 315 A
Current AC-33B (I <sub>e</sub> )	
Rated Operational Power	(380 415 V) 160 kW
AC-23A (P <sub>e</sub> )	(500 V) 220 kW
Companyional Francis	(690 V) 315 kW
Conventional Free-air Thermal Current (Ith)	q = 40 °C 315 A
Conventional Thermal	Fully Enclosed 315 A
Current (I <sub>the</sub> )	runy Enclosed 313 A
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	
)	
Rated Insulation Voltage $(\text{U}_{i})$	1000 V
Rated Operational Voltage	1000 V
Rated Short-time	for 1 s 15 kiloampere rms
Withstand Current (I <sub>cw</sub> )	
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating	Mechanism at the End of the Switch
Mechanism	04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Transition Type	Fast

## **Environmental**

Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303004D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0203

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm
Package Level 1 Depth / Length	325 mm
Package Level 1 Height	218 mm
Package Level 1 Gross	7.545 kg
Weight	16.63 lb
Package Level 1 EAN	6417019401966

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

