


## PRODUCT-DETAILS

# OS800D04N2K

## OS800D04N2K SWITCH FUSE



### General Information

|                       |                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------|
| Extended Product Type | OS800D04N2K                                                                                              |
| Product ID            | 1SCA108722R1001                                                                                          |
| EAN                   | 6417019419510                                                                                            |
| Catalog Description   | OS800D04N2K SWITCH FUSE                                                                                  |
| Long Description      | Switch Fuses,Front Operated,4-pole,04 (Left Side),DIN,3,Direct mounted handle,Switched - With Solid Link |

### Ordering

|                       |              |
|-----------------------|--------------|
| Customs Tariff Number | 85365080     |
| Country of Origin     | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC311113D0203 |
| Instructions and Manuals          | 1SCC311016M0210 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 431 mm |
| Product Net Height | 306 mm |

|                            |                      |
|----------------------------|----------------------|
| Product Net Depth / Length | 233 mm               |
| Product Net Weight         | 19.35 kg<br>42.66 lb |

## Technical

|                                                      |                                                                                                |
|------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )           | (500 V) 800 A<br>(690 V) 800 A                                                                 |
| Rated Operational Current AC-22A ( $I_e$ )           | (380 ... 415 V) 800 A<br>(500 V) 800 A<br>(690 V) 800 A                                        |
| Rated Operational Current AC-23A ( $I_e$ )           | (380 ... 415 V) 800 A<br>(500 V) 800 A<br>(690 V) 800 A                                        |
| Rated Operational Power AC-23A ( $P_e$ )             | (220 ... 240 V) 250 kW<br>(400 V) 450 kW<br>(415 V) 450 kW<br>(500 V) 560 kW<br>(690 V) 710 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ )   | q = 40 °C 800 A                                                                                |
| Conventional Thermal Current ( $I_{the}$ )           | Fully Enclosed 720 A                                                                           |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )        | 12 kV                                                                                          |
| Rated Insulation Voltage ( $U_i$ )                   | 1000 V                                                                                         |
| Rated Operational Voltage                            | 500 V                                                                                          |
| Rated Short-time Withstand Current ( $I_{cw}$ )      | for 1 s 18 kiloampere rms                                                                      |
| Rated Conditional Short-Circuit Current ( $I_{nc}$ ) | (690 V) 80 kA                                                                                  |
| Power Loss                                           | at Rated Operating Conditions per Pole 65 W                                                    |
| Pollution Degree                                     | 3                                                                                              |
| Handle Type                                          | Direct mounted handle included                                                                 |
| Fourth Pole Position                                 | Right Side                                                                                     |
| Fourth Pole Type                                     | Switched - With Solid Link                                                                     |
| Switches Operating Mechanism                         | 04 (Left Side)                                                                                 |
| Position of Line Terminals                           | Top In - Bottom Out, Bottom In - Top Out                                                       |
| Fuse Size                                            | 3                                                                                              |
| Fuse System                                          | DIN                                                                                            |
| Operating Mode                                       | Front Operated                                                                                 |
| Standards                                            | IEC 60947-3                                                                                    |
| Mounting Type                                        | Base mounting                                                                                  |
| Number of Poles                                      | 4                                                                                              |
| Cable Cross-Section                                  | 2.5 ... 25 mm <sup>2</sup>                                                                     |
| Terminal Type                                        | Lug terminals                                                                                  |
| Terminal Width                                       | 39 mm                                                                                          |
| Tightening Torque                                    | 50 ... 75 N·m                                                                                  |
| Fuse Type                                            | DIN                                                                                            |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

| Certificates and Declarations (Document Number) |                                                                   |
|-------------------------------------------------|-------------------------------------------------------------------|
| CCC Certificate                                 | CCC OS630-800 2016                                                |
| Declaration of Conformity - CE                  | 1SCC311112D2704                                                   |
| DNV GL Certificate                              | 1SCC311131D0202                                                   |
| EAC Certificate                                 | EAC<br>OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf |
| Instructions and Manuals                        | 1SCC311016M0210                                                   |
| RoHS Information                                | 1SCC311112D2704                                                   |

| Container Information          |                      |
|--------------------------------|----------------------|
| Package Level 1 Units          | box 1 piece          |
| Package Level 1 Width          | 328 mm<br>12.91 in   |
| Package Level 1 Depth / Length | 453 mm<br>17.83 in   |
| Package Level 1 Height         | 310 mm<br>12.2 in    |
| Package Level 1 Gross Weight   | 20.29 kg<br>44.73 lb |
| Package Level 1 EAN            | 6417019419510        |

| Classifications            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 4                     | EC001040 - Fuse switch disconnecter                        |
| ETIM 5                     | EC001040 - Fuse switch disconnecter                        |
| ETIM 6                     | EC001040 - Fuse switch disconnecter                        |
| ETIM 7                     | EC001040 - Fuse switch disconnecter                        |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Switches → Switch Fuses

