

PRODUCT-DETAILS

OT2000E13W8 OT2000E13W8 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT2000E13W8
Product ID	1SCA109928R1001
EAN	6417019431871
Catalog Description	OT2000E13W8 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector, handle and shaft are not included, wide phase distance, terminal bolt kit included
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301078M0205
Dimensions	
Product Net Width	775.5 mm

OT2000E13W8 2

Product Net Height	376.5 mm
Product Net Depth / Length	145.5 mm
Product Net Weight	35.8 kg 78.8 lb

Technical	
Rated Operational Current AC-21B (I _e)	(380 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Rated Operational Current AC-22B (I_e)	(380 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 2000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 176 kA
Rated Short-time Withstand Current ($I_{\rm CW}$)	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 55 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 13 (Between the Poles)
Distance Between Phases	Phase distance 185 mm
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	Wide phase distance 185
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 5075 N·m
Mechanical Durability	6000
Lock Type	No

nmental	

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and	d Dec	larations	(Document	Numbe	r)
------------------	-------	-----------	-----------	-------	----

Declaration of Conformity - CE	1SCC301176D2702
DNV GL Certificate	1SCC301184D0203

OT2000E13W8 3

Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301078M0205
RoHS Information	1SCC301149D0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	444 mm
	17.48 in
Package Level 1 Depth /	714 mm
Length	28.11 in
Package Level 1 Height	385 mm
	15.16 in
Package Level 1 Gross	39 kg
Weight	18 lb
Package Level 1 EAN	6417019431871

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Disconnectors

