

PRODUCT-DETAILS

OS100GJ22FP

OS100GJ22FP FUSIBLE DISCONNECT SWITCH



General Information

Extended Product Type	OS100GJ22FP
Product ID	1SCA114636R1001
EAN	6417019469973
Catalog Description	OS100GJ22FP FUSIBLE DISCONNECT SWITCH
Long Description	Switch Fuses,Front Operated,4-pole,22 (Between the Poles),Class J,100 A,Handle and shaft included,Switched - Fusible Pole

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311137D0201
Instructions and Manuals	1SCC110037M0206

Dimensions

Product Net Width	182 mm
Product Net Height	172 mm

Product Net Depth / Length	105 mm
Product Net Weight	2.5 kg 5.51 lb

Technical

Rated Operational Current AC-21A (I _e)	(500 V) 100 A (690 V) 100 A
Rated Operational Current AC-22A (I _e)	(500 V) 100 A (690 V) 100 A
Rated Operational Current AC-23A (I _e)	(500 V) 100 A (690 V) 100 A
Rated Operational Power AC-23A (P _e)	(220 ... 240 V) 45 kW (400 V) 75 kW (415 V) 75 kW (500 V) 90 kW (690 V) 132 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 160 A
Conventional Thermal Current (I _{the})	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 5 kiloampere rms
Rated Conditional Short-Circuit Current (I _{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 12 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Fourth Pole Type	Switched - Fusible Pole
Switches Operating Mechanism	22 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	100 A
Fuse System	Class J
Operating Mode	Front Operated
Standards	UL98 IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	2.5 ... 25 mm ²
Terminal Type	Lug terminals
Terminal Width	20 mm
Fuse Type	J

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 240 V) 30 Hp (acc. to UL 480 V) 60 Hp (acc. to UL 600 V) 75 Hp
Ampere Rating UL/CSA	100 A
Tightening Torque UL/CSA	Wire-Clamp 120 in·lb Cable Lug 50 in·lb

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS100-160G_ 2015.pdf
Declaration of Conformity - CE	1SCC311137D2703
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC110037M0206
RoHS Information	1SCC311137D2703

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	260 mm 10.2 in
Package Level 1 Depth / Length	290 mm 11.4 in
Package Level 1 Height	190 mm 7.5 in
Package Level 1 Gross Weight	2.8 kg 6.1 lb
Package Level 1 EAN	6417019469973

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

