

PRODUCT-DETAILS

OT2500EM03W8P

OT2500EM03W8P SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT2500EM03W8P
Product ID	1SCA115843R1001
EAN	6417019481081
Catalog Description	OT2500EM03W8P SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, horizontally base mounted earthing switch with black IP65 handle and shaft, wide phase distance, terminal bolt kit included

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301077M0204

Dimensions

Product Net Width	605.5 mm
-------------------	----------

Product Net Height	376.5 mm
Product Net Depth / Length	234 mm
Product Net Weight	28.7 kg 63.3 lb

Technical

Rated Operational Current AC-21B (I_g)	(380 ... 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Rated Operational Current AC-22B (I_g)	(380 ... 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 2500 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 176 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 85 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	03 (Left Side) Mechanism turned 90 degrees
Distance Between Phases	Phase distance 185 mm
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	Wide phase distance 185
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50...75 N·m
Mechanical Durability	6000
Lock Type	Yes
Utilization	Earthing Switch Use

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301176D2702
DNV GL Certificate	1SCC301184D0203

Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301077M0204
RoHS Information	1SCC301149D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	444 mm 17.48 in
Package Level 1 Depth / Length	714 mm 28.11 in
Package Level 1 Height	385 mm 15.16 in
Package Level 1 Gross Weight	33 kg 15 lb
Package Level 1 EAN	6417019481081

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3601485

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

