

PRODUCT-DETAILS

## OSM125GB3M230C OSM125GB3M230C MOTORIZED SWITCH FUSE



General Information	
Extended Product Type	OSM125GB3M230C
Product ID	1SCA116677R1001
EAN	6417019487731
Catalog Description	OSM125GB3M230C MOTORIZED SWITCH FUSE
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A1250A), male connectors for control circuit and a handle and spare fuse storage clip.
Ordoring	
Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311029M0203
Dimensions	
Product Net Width	290 mm
Product Net Height	206 mm

OSM125GB3M230C 2

Product Net Depth / Length	140 mm
Product Net Weight	5.5 kg 12.13 lb

Technical	
Rated Operational Current AC-21A (I <sub>e</sub> )	(500 V) 125 A (380 415 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A ( $I_e$ )	(500 V) 125 A (380 415 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A ( $I_e$ )	(380 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(380 415 V) 55 kW (500 V) 75 kW (690 V) 110 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 125 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 5 kiloampere rms
Rated Conditional Short- Circuit Current (I <sub>nc</sub> )	(690 V) 80 kA
Motor Operational Voltage	220 240 V AC
Power Loss	at Rated Operating Conditions per Pole 5 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Switches Operating Mechanism	03 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	A2-A4
Fuse System	British Standard
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Fuse Type	BS

Environmental	
Environmental Information	1SCC311002D0201

Certificates and Declarations (Document Number)		
Environmental Information	1SCC311002D0201	
Instructions and Manuals	1SCC311029M0203	

OSM125GB3M230C 3

Package Level 1 Units	box 1 piece
Package Level 1 Width	215 mm 8.46 in
Package Level 1 Depth / Length	395 mm 15.55 in
Package Level 1 Height	215 mm 8.46 in
Package Level 1 Gross Weight	6.5 kg 2.9 lb
Package Level 1 EAN	6417019487731

CI	assifications	

Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Motorized Switch Fuses

