

PRODUCT-DETAILS

OS1200L02P

OS1200L02P FUSIBLE DISCONNECT SWITCH



General Information

Extended Product Type	OS1200L02P
Product ID	1SCA116925R1001
EAN	6417019489964
Catalog Description	OS1200L02P FUSIBLE DISCONNECT SWITCH
Long Description	Switch Fuses,Front Operated,2-pole,02 (Left Side),Class L,1200 A,Handle and shaft included,

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311127D0202
Instructions and Manuals	1SCC311022M0207

Dimensions

Product Net Width	319 mm
Product Net Height	426 mm

Product Net Depth / Length	294 mm
Product Net Weight	22.36 kg 49.3 lb

Technical

Rated Operational Current AC-21B (I _e)	(500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 1250 A
Rated Operational Current AC-22B (I _e)	(500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 1000 A
Rated Operational Current AC-23B (I _e)	(500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P _e)	(220 ... 240 V) 315 kW (400 V) 560 kW (415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 1250 A
Conventional Thermal Current (I _{the})	Fully Enclosed 1000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 40 kiloampere rms
Rated Conditional Short-Circuit Current (I _{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 110 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Switches Operating Mechanism	02 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	1200 A
Fuse System	Class L
Operating Mode	Front Operated
Standards	UL98 IEC 60947-3
Mounting Type	Base mounting
Number of Poles	2
Terminal Type	Lug terminals
Terminal Width	50 mm
Fuse Type	L

Technical UL/CSA

Ampere Rating UL/CSA	1200 A
Tightening Torque UL/CSA	Wire-Clamp 500 in·lb Cable Lug 480 in·lb

Environmental

RoHS Status

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS1200-1250 2015.pdf
Declaration of Conformity - CE	1SCC311127D2703
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_ f
Instructions and Manuals	1SCC311022M0207
RoHS Information	1SCC311127D2703

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	339 mm 13.35 in
Package Level 1 Depth / Length	444 mm 17.48 in
Package Level 1 Height	338 mm 13.31 in
Package Level 1 Gross Weight	24.29 kg 53.55 lb
Package Level 1 EAN	6417019489964

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

