

323 mm

PRODUCT-DETAILS

Dimensions
Product Net Width

OT200E33WCPOT200E33WCP CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT200E33WCP
Product ID	1SCA118607R1001
EAN	6417019503264
Catalog Description	OT200E33WCP CHANGE-OVER SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201

Product Net Height	150 mm
Product Net Depth / Length	160 mm
Product Net Weight	5.88 kg 12.96 lb

Technical	
Rated Operational	(380 415 V) 200 A
Current AC-21A (I _e)	(500 V) 200 A
	(690 V) 200 A
Rated Operational	(380 415 V) 200 A
Current AC-22A (I _e)	(500 V) 200 A
	(690 V) 200 A
Rated Operational	(380 415 V) 200 A
Current AC-23A (I _e)	(500 V) 200 A (690 V) 200 A
Rated Operational	(380 415 V) 200 A
Current AC-31B (I _e)	(380 413 V) 200 P
Rated Operational	(380 415 V) 200 A
Current AC-33B (I _e)	(*** m *** *, *** *)
Rated Operational Power	(380 415 V) 110 kW
AC-23A (P _e)	(500 V) 132 kW
	(690 V) 200 kW
Conventional Free-air	q = 40 °C 200 A
Thermal Current (Ith)	
Conventional Thermal	Fully Enclosed 200 A
Current (I _{the})	
Rated Impulse	12 kV
Withstand Voltage (U _{imp}	
)	
Rated Insulation Voltage (U _i)	1000 V
	10001
Rated Operational Voltage	1000 V
Rated Short-time	for 1 s 8 kiloampere rms
Withstand Current (I _{cw})	Tot 130 kiloampere mis
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating	Mechanism Between the Poles
Mechanism	33 (Between the Poles)
Distance Between	Wide phase distance
Phases	wide priase distance
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	Top III Bottom Out, Bottom III Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	6
Degree of Protection	Front IP20
	
Transition Type	Open

Environmental

Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)

Declaration of 1SCC303002D0202

Conformity - CE

Environmental	1SCC303050D0201
Information	100000000000000000000000000000000000000
Instructions and	1SCC303008M0203
Manuals	100000000000000000000000000000000000000

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	215 mm
Package Level 1 Depth / Length	395 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	6.82 kg 15.04 lb
Package Level 1 EAN	6417019503264

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

