

323 mm

170 mm

PRODUCT-DETAILS

**Product Net Width** 

Product Net Height

## **OT250E33WCP**OT250E33WCP CHANGE-OVER SWITCH



OT250E33WCP
1SCA118608R1001
6417019503271
OT250E33WCP CHANGE-OVER SWITCH
OT250E33WCP CHANGE-OVER SWITCH, Handle and shaft included, Open transition
1 piece
85365080
Finland (FI)
1SCC303003C0201
1SCC303008M0203

Product Net Depth / Length	160 mm
Product Net Weight	5.88 kg 12.96 lb

Technical	
Rated Operational	(380 415 V) 250 A
Current AC-21A (I <sub>e</sub> )	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-22A (I <sub>e</sub> )	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-23A (I <sub>e</sub> )	(500 V) 250 A (690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-31B (I <sub>e</sub> )	
Rated Operational Current AC-33B (I <sub>e</sub> )	(380 415 V) 250 A
Rated Operational Power	(380 415 V) 140 kW
AC-23A (P <sub>e</sub> )	(500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 250 A
Conventional Thermal	Fully Enclosed 250 A
Current (I <sub>the</sub> )	Tully Enclosed 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 8 kiloampere rms
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 33 (Between the Poles)
Distance Between Phases	Wide phase distance
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	6
Degree of Protection	Front IP20
Transition Type	Open

Environmental	
Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of	1SCC303001D2704
Conformity - CE	

Environmental Information	1SCC303050D0201
Instructions and	1SCC303008M0203
Manuals	

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	215 mm
Package Level 1 Depth / Length	395 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	6.82 kg 15.04 lb
Package Level 1 EAN	6417019503271

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

