

PRODUCT-DETAILS

OSM630B4N1M230C

OSM630B4N1M230C MOTORIZED SWITCH FUSE



General Information

Extended Product Type	OSM630B4N1M230C
Product ID	1SCA118791R1001
EAN	6417019504773
Catalog Description	OSM630B4N1M230C MOTORIZED SWITCH FUSE
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A...1250A), male connectors for control circuit and a handle and spare fuse storage clip.

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311029M0203

Dimensions

Product Net Width	575 mm
Product Net Height	304 mm

Product Net Depth / Length	306 mm
Product Net Weight	25.2 kg

Technical

Rated Operational Current AC-21A (I_g)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A (I_g)	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-23A (I_g)	(500 V) 630 A (380 ... 415 V) 630 A (690 V) 630 A
Rated Operational Power AC-23A (P_g)	(380 ... 415 V) 355 kW (500 V) 450 kW (690 V) 630 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40^\circ\text{C}$ 630 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 18 kiloampere rms
Rated Conditional Short- Circuit Current (I_{nc})	(690 V) 80 kA
Motor Operational Voltage	220 ... 240 V AC
Power Loss	at Rated Operating Conditions per Pole 46 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Left Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	04 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	C1-C2
Fuse System	British Standard
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Fuse Type	BS

Environmental

Environmental Information	1SCC311002D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC311154D2703
Environmental Information	1SCC311002D0201
Instructions and Manuals	1SCC311029M0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	440 mm
Package Level 1 Depth / Length	700 mm
Package Level 1 Height	565 mm
Package Level 1 Gross Weight	25.2 kg
Package Level 1 EAN	6417019504773

Classifications	
Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Switches → Motorized Switch Fuses

