

253 mm

197 mm

PRODUCT-DETAILS

Product Net Width

Product Net Height

OSM32GD4N2M230COSM32GD4N2M230C MOTORIZED SWITCH FUSE



OSM32GD4N2M230C
1SCA118822R1001
6417019504889
OSM32GD4N2M230C MOTORIZED SWITCH FUSE
Including a handle for manual operation, including protected tunnel terminals, male connectors for control circuit and a handle and spare fuse storage clip
85365080
Finland (FI
1SCC311013C0201
1SCC311029M0203

OSM32GD4N2M230C 2

Product Net Depth / Length	138 mm
Product Net Weight	4.87 kg 10.74 lb

Technical	
Rated Operational	(500 V) 32 A
Current AC-21A (I _e)	(380 415 V) 32 A (690 V) 32 A
Rated Operational	(380 415 V) 32 A
Current AC-22A (I _e)	(500 V) 32 A (690 V) 32 A
Rated Operational	(500 V) 32 A
Current AC-23A (I _e)	(380 415 V) 32 A (690 V) 32 A
Rated Operational Power	(380 415 V) 15 kW
AC-23A (P _e)	(500 V) 18.5 kW (690 V) 22 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 32 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (Ui)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 2.5 kiloampere rms
Rated Conditional Short- Circuit Current (I _{nc})	(690 V) 80 kA
Motor Operational Voltage	220 240 V AC
Power Loss	at Rated Operating Conditions per Pole 1 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	04 (Left Side)
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	
Fuse Size	000
Fuse System	DIN
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Screw Terminals
Fuse Type	DIN

Environmental 1SCC311002D0201

Certificates and Declarations (Document Number)

Environmental Information

Information

1SCC311002D0201

Instructions and Manuals 1SCC311029M0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm
	12.91 in
Package Level 1 Depth /	365 mm
Length	14.37 in
Package Level 1 Height	260 mm
	10.24 in
Package Level 1 Gross	5.95 kg
Weight	13.12 lb
Package Level 1 EAN	6417019504889

Classifications	
Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Motorized Switch Fuses

