

PRODUCT-DETAILS

OSM400D4N2M230C

OSM400D4N2M230C MOTORIZED SWITCH FUSE



General Information

Extended Product Type	OSM400D4N2M230C
Product ID	1SCA118842R1001
EAN	6417019505114
Catalog Description	OSM400D4N2M230C MOTORIZED SWITCH FUSE
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A...1250A), male connectors for control circuit and a handle and spare fuse storage clip.

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311029M0203

Dimensions

Product Net Width	468 mm
Product Net Height	251 mm
Product Net Depth / Length	230 mm
Product Net Weight	12.9 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I_e)	(500 V) 400 A (380 ... 415 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(500 V) 400 A (380 ... 415 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40^\circ\text{C}$ 400 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 14 kiloampere rms
Rated Conditional Short- Circuit Current (I_{nc})	(690 V) 80 kA
Motor Operational Voltage	220 ... 240 V AC
Power Loss	at Rated Operating Conditions per Pole 30 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	04 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	0, 1, 2
Fuse System	DIN
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Fuse Type	DIN

Environmental

Environmental Information	1SCC311002D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC311153D2703
Environmental Information	1SCC311002D0201
Instructions and Manuals	1SCC311029M0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	310 mm
Package Level 1 Depth / Length	560 mm
Package Level 1 Height	330 mm
Package Level 1 Gross Weight	12.9 kg
Package Level 1 EAN	6417019505114

Classifications

Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Motorized Switch Fuses

