

197 mm

PRODUCT-DETAILS

**Product Net Height** 

## **OSM63GD4N2M230C**OSM63GD4N2M230C MOTORIZED SWITCH FUSE



General Information	
Extended Product Type	OSM63GD4N2M2300
Product ID	1SCA118865R100
EAN	6417019505190
Catalog Description	OSM63GD4N2M230C MOTORIZED SWITCH FUSE
Long Description	Including a handle for manual operation, including protected tunnel terminals, male connectors for control circuit and a handle and spare fuse storage clip
Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC311013C020
Instructions and Manuals	1SCC311029M0203
Dimensions	
Product Net Width	253 mm

OSM63GD4N2M230C 2

Product Net Depth / Length	138 mm
Product Net Weight	4.87 kg 10.74 lb

Technical	
Rated Operational	(500 V) 63 A
Current AC-21A (I <sub>e</sub> )	(380 415 V) 63 A (690 V) 63 A
Rated Operational	(380 415 V) 63 A
Current AC-22A (I <sub>e</sub> )	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(500 V) 63 A (380 415 V) 63 A (690 V) 63 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(380 415 V) 22 kW (500 V) 30 kW (690 V) 37 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 63 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>1</sub> )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 2.5 kiloampere rms
Rated Conditional Short- Circuit Current (I <sub>nc</sub> )	(690 V) 80 kA
Motor Operational Voltage	220 240 V AC
Power Loss	at Rated Operating Conditions per Pole 4 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	04 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	000
Fuse System	DIN
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Screw Terminals
Fuse Type	DIN

## Environmental 1SCC311002D0201

## **Certificates and Declarations (Document Number)**

Environmental Information

Information

1SCC311002D0201

Instructions and 1SCC311029M0203 Manuals

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm
	12.91 in
Package Level 1 Depth /	365 mm
Length	14.37 in
Package Level 1 Height	260 mm
	10.24 in
Package Level 1 Gross	5.95 kg
Weight	13.12 lb
Package Level 1 EAN	6417019505190

Classifications	
Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Motorized Switch Fuses

